

## OFF Bure

Tectyl remover

Approved by Byggsvarubedömningen, Sunda Hus, Chemsoft and Trafikverket

### Range of application:

Removal of tectyl graffiti on porous and non-porous surfaces.

### How to use:

Apply OFF Bure and leave for approx. 10 min – 2 hours, depending on temperature. Rinse with water. A suitable temperature and pressure would normally be 90°C and 90-150 bar pressure, depending on the surface type. Duration of painted surfaces: 5-20 min.



**Containers:** 10 or 25 litre, can

**Storage:** Frost-free in original packing

**Dosage:** Concentrate

**pH value:** Neutral

**Consumption:** Approx. 0,1-0,3 litre/m<sup>2</sup>

**ADR:** Not classified as dangerous goods if transported by road or by rail

### Precautions:

Use protective gloves made of butyl or nitrile rubber.

Ensure good ventilation, avoid inhalation of dust.

Use protecting clothing, gloves, visor or glasses in case of contact.

Eye wash facilities and emergency shower must be available when handling this product.

For more information please see the Safety Data Sheet for this particular product.

This product information is intended only as a guideline. MPE International does not accept responsibility for the end result.  
If in doubt, contact MPE International for advice.

**MPE International AB**  
Dalagatan 3B  
S-803 10 Gävle, Sweden

**Phone:**  
+46(0)8-522 99 440

**Email:**  
info@mpei.se

**Web:**  
www.mpei.se

**Org.nr:**  
556722-0420