

SPS Brage

Highly efficient dissolvent

Is in compliance with European Parliament and Council Regulation (EC) no. 1907/2006 concerning the registration, evaluation, authorisation and restriction of chemicals (REACH)

Range of application:

A highly efficient product that solves thick oil, grease and fat a.o. SPS Brage may be used for washing and degreasing of oil preheater, oil tanks, oil filter and heaters.

How to use:

Apply with low pressure to the area that needs cleaning. Leave on for about 5-30 minutes. Mechanical treatment increases the cleaning effect. Wash with water or wipe with a cloth, depending on whether the surface is water resistant or not. SPS Brage has the same fire rating as heating oil and can be burned in existing facility.



Containers: 10 or 25 litre, can

Storage: Frost-free in original packing

Dosage: Concentrate

pH value: Neutral

Consumption: Approx. 0,1-0,3 litre/m²

ADR: Not classified as dangerous goods for use by road or rail transportation

Precautions:

Ensure good ventilation.

Use protecting clothing, gloves, visor or glasses in case of contact.

Eye wash facilities and emergency shower must be available when handling this product.

For more information please see the Safety Data Sheet for this particular product.



Signal word: Danger

This product information is intended only as a guideline. MPE International does not accept responsibility for the end result. If in doubt, contact MPE International for advice.

MPE International AB
Dalagatan 3B
S-803 10 Gävle, Sweden

Phone:
+46(0)8-522 99 440

Email:
info@mpei.se

Web:
www.mpei.se

Org.nr:
556722-0420