

# Status Scientific Controls

gas detection technology...



## LC COMMERCIAL SERIES ~ 8 channel control unit



### FEATURES INCLUDE: -

- Lockable, wall mounting steel enclosure powder coated to RAL7035
- IP65
- Graphic display simultaneously showing reading for each channel and sensor type
- Visual indicators for alarm, fault and power
- Full calibration menu via push buttons on front panel
- Each channel can accept:
  - 2-wire current source 4-20mA
  - 3-wire power plus current source 4-20mA
  - 3-wire pellistor systems

### and output:

- 4-20mA current source proportional to the detected signal
- 4-20mA current sink proportional to the detected signal
- 0-5V voltage output proportional to the detected signal
- 2 Alarm relays per channel
- 1 Common fault relay

## LC8 Control Unit Specification

Size	500mm Wide x 300mm High x 80mm Deep
Weight	7.65 kg
Operating Temp	-10°C to +50°C
Storage Temp	-20°C to +50°C
Humidity Range	0 to 95% R.H. Non-condensing
Input Voltage	18-28V DC, or 100-240V AC 50/60
Environmental Rating	IP65

User Interface	
Display	LCD Graphics with Backlight
Keyboard	4 button multifunction keypad
LED Indications Option 1	Red      Indicates alarm condition. Yellow   Indicates fault condition. Green    Indicates power ON
LED Indications Option 2	Green    Indicates power ON Red      Indicates alarm level 3 condition. Red      Indicates alarm level 2 condition. Red      Indicates alarm level 1 condition. Yellow    Indicates fault condition.

Input Modules	
Number of channels	8 max
Signal Inputs 8 Max	4-20mA Current Loop from 24V source. 4-20mA Current Loop sink to 0V. 3-Wire Pellistor Systems.
Analogue Output 8 Max	4-20mA Current source proportional to detected signal. 4-20mA Current sink proportional to detected signal. 1-5V Voltage output proportional to detected signal.
Relays – 18 Max	1 relay assigned to alarm level 1 - channels 1 to 8. 1 relay assigned to alarm level 2 - channels 1 to 8. 1 relay assigned to common alarm level 3. 1 relay assigned to fault condition.
Contacts Rating	Single Pole Changeover Contacts (voltage free). 5A 240V AC.

Power Supply	
Fuse 1 (AC Input)	T1.0A
Fuse 2 (24VDC input)	T500mA

Designed and Manufactured in the UK

**Status Scientific Controls Ltd**  
 Hermitage Lane Industrial Estate  
 Kings Mill Way, Mansfield  
 Nottinghamshire NG18 5ER  
 Tel: (44) 01623 651381 Fax: (44) 01623 427816  
 email: [sales@status-scientific.com](mailto:sales@status-scientific.com)  
[www.status-scientific.com](http://www.status-scientific.com)