ThinTrack™

Ultra-thin and compact GPS tracker














Suitable for insertion into envelopes or plastic pouches used for shipping documentation, this re-usable, waterproof device has a battery life of many years and is ideal for tracking individual items such as packages and letter where accurate positioning would not have been practical before.

ThinTrack™ is an ultra-low profile, compact GPS tracker solution that integrates LTE-M/ modem, antenna, NB-IoT, battery, eSIM and all necessary electronics into a device that measures only 82x35x3/5/8 mm and weighs only 13/16/20g.





Other potential applications for ThinTrack™ include the tracking and theft prevention of luggage, high value designer goods and tools.



Powered by





Specification:

Ultra-thin & compact design
Cellular LTE-M/NB-IoT
Multi-year battery life
Integrated Antenna, Battery & eSIM
GPS technology powered by Nestwave
(Optional Wi-Fi) Waterproof IP54/65
Reusable & activable / rechargeable

Asset tracking & luxury solution

- Discretion
- Theft prevention
- Easy to use
- Multi-application
- Reusable (rechargeable option)

	Specification		
Communication	LTE-M/NB-IoT		
Bands	Worldwide 17 bands coverage		
Protocol	CoAP over UDP		
Outdoor Localisation	Assisted GPS, Galileo*		
Battery	Li-Ion Polymer (LIP) or Li-MnO2		
Time To First Fix (open sky)	0.5 to 2sec		
Accuracy **	3 to 5m		
Shipping mode	Activable via NFC		
Indoor localisation	Wi-Fi Positioning System (Optional)		
Wake-up	Accelerometer, NFC Flight mode		
Temperature sensor	+/- 1.0°		
Compliance	CE, FCC, ROHS, UN38.3		
Rating	IP54 or IP65		
Material	ABS plastic / Polycarbonate		
Operating temperature	-20+60°C		
Charging temperature	0+40°C		

^{*} Galileo available Q3 2022

^{**} CEP 50%



Versions:









	ThinTrack™ Single	ThinTrack™ Ultra	ThinTrack™ Plus	ThinTrack™ Long
	SAM221-0xx	SAM221-1xx	SAM221-2xx	SAM221-5xx
Size / Weight	82.6 x 35.2 x 3.0	82.6 x 35.2 x 3.0	82.2 x 34.8 x 5.0	82.2 x 34.8 x 8.0
	mm -13g	mm -13g	mm - 16g	mm - 20g
Battery	150mAh - Li-Ion	150mAh - Li-lon	600mAh - Li-	1200mAh - Li-
	Polymer (LIP)	Polymer (LIP)	MnO2	MnO2
Recharge	NFC slow recharge (12h)	Wireless charging (2h)	-	-
Shipping mode	Activable via NFC	Activable via NFC	Activable via NFC	Activable via NFC
Autonomy *	Up to 1 year — 1fix/day	Up to 1 year – 1fix/day	3 years – 1fix/day	5 years — 1fix/day
Indoor	Wi-Fi Positionning	Wi-Fi Positionning	Wi-Fi Positionning	Wi-Fi Positionning
localisation	(Option)	(Option)	(Option)	(Option)
Rating,	IP54, CE, FCC,	IP54, CE, FCC,	IP65, CE, FCC,	IP65, CE, FCC,
	ROHS, UN38.3	ROHS, UN38.3	ROHS, UN38.3	ROHS, UN38.3

* At 25°C room temperature





Activation with Secured NFC smartphone application. ThinTrack identification on supervision software with unique ID number



