



Professional battery tester providing highly accurate results with in-built printer

## FEATURES

- **Battery 12 V** : voltage test and state of charge.
- **Starter 12 and 24 V** : test of the start voltage.
- **Alternator 12 and 24 V** : test of no load voltage and charging voltage as well as current undulation during the charge.
- **Printout of the results** using integrated thermal printer (no ink required).

## INSTANT ANALYSIS

- Battery voltage (8 V to 30 V)
- Available starting power
- Charge state and battery health (%)

## BATTERY TYPES

- Compatible with **multiple types of lead-acid batteries** ranging from **7 to 240 Ah** :

- VRLA / GEL / AGM FLAT / AGM SPIRAL / SLI sealed batteries
- STANDARD LIQUID batteries
- START / STOP batteries (EFB / AGM)

### ■ Operating range :

EN : 40 > 1885 CCA

DIN : 25 > 1120 CCA

SAE/CCA : 40 > 2000 CCA

JIS : japanese battery

IEC : 30 > 1320 CCA (international standard)

CA/MCA : 50 > 2400 CCA (marine battery)

## HIGHLY ACCURATE

- Automatic compensation for external temperature.
- Advanced dynamic resistance measurement technology minimises battery discharge and displays an accurate result which is unaffected by :
  - The surface charge
  - Vehicle consumers (lights, various indicators, etc)
  - Contact imperfections (worn out terminals / lugs, unfastened lugs, etc)

## PRACTICAL

- Insulated clamps
- Large backlit display screen
- Adjustable screen brightness
- Full test report showing date/time and personalised name
- Multilingual interface (10 languages)
- Protected against polarity reversal.
- ABS case (acid resistant) and protection against shock
- Power supply : 1 battery CR2032



Supplied in a case with 1 paper roll (large paper format - 2 inches).

|         |           | TEST      |                 |                                    |     | RESULT  |   | TEMPERATURE COMPENSATION | cm     |     | kg |
|---------|-----------|-----------|-----------------|------------------------------------|-----|---------|---|--------------------------|--------|-----|----|
| Battery |           | Battery A | Battery V       | CHARGING & STARTING SYSTEM VEHICLE |     |         |   |                          |        |     |    |
| 12 V    | 7 >240 Ah | •         | •<br>min<br>8 V | 12 V<br>24 V                       | 1 s | instant | • | 23,5 x<br>10,2 x 6,8     | 120 cm | 0.7 |    |