



Professional battery tester providing highly accurate measurements.

FEATURES

- **Battery 12 V:** test of the voltage and state of charge.
- **Starter 12 & 24 V:** test of the start voltage.
- **12 & 24 V Alternator:** tests no load voltage and charging voltage as well as current undulation during the charge.

INSTANT ANALYSIS

- Battery voltage (8 V to 30 V)
- Available starting power
- Charge state and battery health (%)

BATTERY TYPES

- Compatible with **3 types of lead-acid battery** ranging from **7 to 230 Ah**:
 - VRLA / GEL / AGM FLAT / AGM SPIRAL sealed batteries
 - STANDARD LIQUID batteries
 - START / STOP batteries (EFB/AGM)

Operating ranges :

- 🇪🇺 EN : 40 > 1885 CCA
- 🇩🇪 DIN : 25 > 1120 CCA
- 🇺🇸 SAE/CCA : 40 > 2000 CCA
- 🇯🇵 JIS : japanese battery
- 🌐 IEC : 30 > 1320 CCA (international standard)
- CA/MCA : 50 > 2400 CCA (marine battery)



HIGHLY ACCURATE

- Automatic compensation of external temperature.
- The dynamic resistance measuring technology minimises battery discharge and displays a reliable result unaffected by:
 - surface charge
 - vehicle consumers (lights, various indicators, etc)
 - contact defaults (worn out terminals/ lugs, unfastened lugs, etc)

PRACTICAL

- Insulated clamps
- Large backlit «4-line» display for better viewing
- Adjustable screen brightness
- Retroactive «ENTER» key
- Multilingual interface (10 languages)
- Reverse polarity protection
- ABS housing (acid-proof) + shock protection

		TEST				RESULT		TEMPERATURE COMPENSATION	cm	
Battery		Battery A	Battery V	CHARGING & STARTING SYSTEM VEHICLE						
12 V	7 >230 Ah	•	• min 8 V	12 V 24 V	1 s	instant	•	13,8 x 9,6 x 3	40 cm	