

HEAVYPRO



Caratteristiche Generali

- Carrello a due ruote completo di manico
- Pompa a 3 pistoni in ceramica, con sistema biella-manovella
- Valvola di bypass automatica con azzeramento della pressione nella testa pompa
- Motore elettrico monofase a induzione con protezione termica
- Regolazione della pressione
- Manometro
- Aspirazione detergente incorporata
- Aspirazione detergente regolabile
- Funzione autoadescante
- Tubo rinforzato con treccia in acciaio (10 m)

General Features

- Two-wheel trolley unit with handle
- Triplex pump with ceramic pistons and connecting rod system
- Automatic bypass valve with pressure shut-off at pump head
- Single-phase induction motor with thermal protection
- Pressure adjustment
- Pressure gauge
- Built-in detergent suction
- Adjustable detergent injector
- Self-priming function
- Steel braided hose (10 m)

930	960	980
HRC	HRC	HRR
INDUCTION	ROD-CRANK	BRASS
MAX 60°C 140°F	IPX5-S1	SPF Self Priming FUNCTION
	TSS Total Stop SYSTEM	TST Total Stop SYSTEM
	930.960	980

MOD	COD	 MAX				 MAX								 KG NET
		bar max	bar work	psi max	psi work	l/h work	gph work	hp	kW	kW work	rpm	Hz	V	kg
930	14261	150	120	2175	1740	630	166	3	2,2	3	1450	50	230~	43,6
960	15479	200	180	2900	2610	840	221	6,1	4,5	5	1450	50	400 3~	45,5
980	15480	230	200	3335	2900	900	238	7,5	5,5	7,4	1450	50	400 3~	52,2

Accessori standard / Standard accessories



codice / code	46880 (930.960)	47039 (980)	41929 (930)	46221 (56 cm) (960.980)	3960970 (10 m) (930) 3961050 (10 m) (960.980)	3086 (960/980 - 15045)
entrata inlet	M22x1,5 M 14 mm	M22x1,5 M 14 mm	M22x1,5 M	M22x1,5 M	M22x1,5 F	1/4 NPT M
uscita outlet	M22x1,5 F	M22x1,5 F	-	1/4 NPT F	M22x1,5 F	-

OPTIONAL / OPZIONALE
Cod. 46904

