



MAXIMA 160 SYNERGIC 230V



Overview

MAXIMA 160 SYNERGIC 230V

cod. 816085

Microprocessor controlled MIG-MAG/FLUX/BRAZING inverter wire welding machine. It allows great versatility in the use of various types of materials (steel, stainless steel, aluminium) and in all possible applications, from maintenance to installation works. The SYNERGIC adjustment of the welding parameters makes the products easy to use and grants excellent results, always, also for the less experienced operator.

Light and compact, it can be easily carried in any intervention place, both inside and outside.

Features:

- Polarity reversal for GAS MIG-MAG/BRAZING welding
- Thermostatic, overvoltage, undervoltage, motorgenerator (+/- 15%) protections.

Fit for NO GAS/Flux welding, it can be transformed into MIG-MAG with the optional kit.

Complete with MIG-MAG torch, work clamp and cable.



MIG-MAG FLUX



CE MARKING



EAC CERTIFICATION



1 PH 230V

Technical data

CODE	CODE 816085	MAX ABSORBED CURRENT	18 A	POWER FACTOR (cosphi)	0,7
SINGLE PHASE MAINS VOLTAGE	230 V	ABSORBED CURRENT AT 60% - MAX	9 A	STEEL WELDING WIRE DIAMETER	0,6 - 0,8 mm
MAINS FREQUENCY	50 / 60 Hz	MAX ABSORBED POWER	2,6 kW	INOX WELDING WIRE DIAMETER	0,8 mm
CURRENT RANGE	20 - 150 A	ABSORBED POWER AT 60%	1,2 kW	ALUMINIUM WELDING WIRE DIAM.	0,8 - 1 mm
MAX CURRENT DC (EN 60974-1) 115 @ 20% A		MAINS FUSE	16 A	FLUX CORED WELDING WIRE DIAM.	0,8 - 1,2 mm



MAXIMA 160 SYNERGIC 230V



DC CURRENT 65 A



EFFICIENCY 86 V



BRAZING WIRE DIAM. 0,8 mm



MAX NO LOAD VOLTAGE 44 V

Included Accessories

CABLE 16 MMQ 1,8 M - 124502

TW160 MIG TORCH 2M - 742402



COLORADO 150B WORK CLAMP 150A - 712001