



TECNICA 211/S 230V ACX PLASTIC C.CASE



Overview

TECNICA 211/S 230V ACX PLASTIC C.CASE

cod. 816122

MMA and TIG inverter, electrode welding machine in direct current (DC) with scratch striking.

Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron, etc.

Features:

- compact and light
- high welding current stability in spite of mains voltage fluctuations
- arc force, hot start and anti-stick devices
- thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections.

Complete with MMA welding accessories and plastic carry case.



MMA TIG DC SCRATCH



CE MARKING



TÜV CERTIFICATION



1 PH 230V



EAC CERTIFICATION

Technical data

CODE	CODE 816122	V₀	MAX NO LOAD VOLTAGE 75 V	η	EFFICIENCY 88 %
V_{1PH}	SINGLE PHASE MAINS VOLTAGE 230 V	A_{MAX}	MAX ABSORBED CURRENT 34 A	φ	POWER FACTOR (cosphi) 0,7
F	MAINS FREQUENCY 50 / 60 Hz	A_{MAX} 60%	ABSORBED CURRENT AT 60% - MAX 19 A	Ø_{DC} MIN/MAX	D. USABLE ELECTRODES IN DC 1,6 - 4 mm
A_{MIN} MAX	CURRENT RANGE 15 - 180 A	P_{MAX}	MAX ABSORBED POWER 5,3 kW	IP	PROTECTION DEGREE IP23



TECNICA 211/S 230V ACX PLASTIC C.CASE



%USE (20°C USE) 65% - 180A



ABSORBED POWER AT 60% 2,9 kW



DIMENSIONS 38 - 48 - 17 cm



MAX CURRENT 170 A - 18 %



MOTORGENERATOR MINIMUM POWER
7 kW



WEIGHT 6,7 kg



CURRENT AT 60% 105 A



MAINS FUSE 16 A

(*)%USE:DATUM CREATED BY TELWIN,

Included Accessories

CABLE TW05V-A 1X025 L=1.80M DINSE - 124589



TOLEDO 250 WORK CLAMP 250A - 712030

PLASTIC CARRY CASE - 322800



DALLAS 300 ELECTRODE HOLDER 300A - 712260