IPC

BLACK IS GREEN™

GS 3/50 OPT W&D MFS

EXCLUSIVE FEATURES

▶ MODERN INDUSTRIAL DESING
▶ STRONG AND LIGHTWEIGHT TROLLEY WITH TOP MANUVRABILITY ON ANY TYPE OF FLOOR
▶ BIG RUBBER WHEELS WITH BREAKES
▶ DIMENSION COMPATIBLE WITH DOORS WIDTH
▶ 3 DOUBLE STAGE MOTORS WITH HIGHEST PERFORMANCE
▶ BEST SEALING OF THE POWERHEAD THANKS TO EXCLUSIVE BUILT-IN GASKET
▶ MODULAR CONFIGURATIONS TO COLLECT SOLID DIRECTLY IN THE TANK WITH A CYCLONIC CONVEYOR CONE, FINE DUST IN MICROFIBER BAG OF HIGH RESISTANCE OR LIQUID WITH A MECHANICAL STOP WHEN THE TANK IS FULL
▶ MANUAL FILTER SHAKER

		GS 3/50 OPT W&D MFS
Code		ASDO13653
TECHNICAL DATA		
Usage		WET & DRY
Number of phases		single phase
Voltage / Frequency	V	220-240/50-60
N. and type of motor		3 x 2 stages
Power	W	2900 - 3300 max
Water lift	mmH$_2$O	2300
Airflow	m^3/h	600
Tank Capacity	l	50
Diameter of inlet	mm	60
Filtering surface	cm^2	12.000 + 2.200
Sound Pressure Level	dB(A)	76
Dimensions (LxWxH)	mm	580x700x1150
Weight	Kg	68

STANDARD EQUIPMENT

CODE: FTDP88585
CLASS L STAR-SHAPED FILTER 12.000 cm^2

CODE: FTDP00223
PCB PREFILTER WITH CONDUCTIVE CARBON FOILS

CODE: FTDP00553
HEPA H14 CARTRIDGE 2.200 cm^2

CODE: -
CLASS M FLEECE BAG

CODE: PMVR06689
CONVEYOR CONE FOR CYCLONIC EFFECT AND FILTER PROTECTION

CODE: KTRI04157
FLOATING SYSTEM FOR LIQUID RECOVERY

OPTIONAL ACCESSORIES

Class M Star shaped filter 12.000 cm^2 resistant to 150°C	KTRI02483
Washable polyester cartridge (available as spare part) 3.000 cm^2	FTDP44260
Class M fleece bag -10 Pcs	KTRI05204
Mesh filter	FTDP28755
Fixing system for Mesh filter and cartridge	MPVR28723
Complete multipurpose premium tool kit 3 m ø38 mm	PMDT01227
Complete multipurpose premium tool kit 4 m ø50 mm	PMDT01228
Complete static dissipative tool kit 5 m ø50 mm	PMDT01192
Complete Oil&Abrasives Tool kit 4 m Ø38 mm	PMDT00928
Anti-Static tool kit Ø38-60 mm	PMDT00326

PLANET 1/50 OPT

EXCLUSIVE FEATURES

▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
▶ DETACHABLE TANK AND SOLID CART
▶ MANUAL FILTER SHAKER
▶ BIG AND BRAKED WHEELS
▶ STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE
▶ TURBINE WITH PERFECT PERFORMANCE

		PLANET 1/50 OPT
Code		ASID01200
TECHNICAL DATA		
Usage		DRY
Number of phases		single phase
Voltage	V	230/50
N. and type of turbine		1xsingle stage
Power	W	1500
Water lift	mmH$_2$O	1800
Airflow	m^3/h	220
Tank Capacity	l	50
Diameter of inlet	mm	60
Filtering surface	cm^2	12.000
Sound Pressure Level	dB(A)	74
Dimensions (LxWxH)	mm	600x660x1600
Weight	Kg	65

STANDARD EQUIPMENT

CODE: FTDP88585
POLYESTER MAIN FILTER 12.000 cm^2

CODE: FTDP00223
POLYCARBON PREFILTER

OPTIONAL ACCESSORIES

Basic tool kit Ø38-60 mm	PMDT00325
Anti-Static tool kit Ø38-60 mm	PMDT00326
Basic tool kit Ø50-60 mm	PMDT00443
Anti-Static tool kit Ø50-60 mm	PMDT00436

Complete descriptions and compositions available at pages 213-223

Information about waterlift and airflow refers to motors performances. Specifications, descriptions and pictures are supplied as indicative: rights to technical modifications reserved without prior notice.