



SCRUBBER DRIERS - WALK BEHIND

# CT70

MAX PRODUCTIVITY

3150 m<sup>2</sup>/h

BATTERIES RUNNING TIME

2,5 h

WATER TANK RUNNING TIME

60' working session



ONE BRUSH VERSION



ROLLER VERSION



BATTERIES AND BATTERY CHARGER NOT INCLUDED

MOST FREQUENTLY USE



INNOVATIONS



SPECS



INTUITIVE CONTROL PANEL



SEPARATE DETERGENT DOSING SYSTEM. (OPTIONAL)



ANTI-FOAM SYSTEM WITH SPECIAL ELECTROMECHANICAL SUCTION MOTOR PROTECTION

## TECHNICAL DATA

|   |                   | CT70 B55           | CT70 BT55          | CT70 BT60          | CT70 BT70          | CT70 BT85          | CT70 BT55 R        | CT70 BT70 ECS      |
|---|-------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Code                                    |                   | LPTB01414          | LPTB01416          | LPTB01417          | LPTB01418          | LPTB01419          | LPTB01420          | LPTB02379          |
| <b>PERFORMANCE</b>                      |                   |                    |                    |                    |                    |                    |                    |                    |
| Max theoretical productivity            | m <sup>2</sup> /h | 1925               | 2475               | 2700               | 3150               | 3825               | 2475               | 3150               |
| Cleaning path                           | mm                | 550                | 550                | 600                | 700                | 850                | 550                | 700                |
| Water tank capacity (solution recovery) | l                 | 70/75              | 70/75              | 70/75              | 70/75              | 70/75              | 70/75              | 70/75              |
| Max running time                        | min               | 78                 | 78                 | 78                 | 78                 | 78                 | 78                 | 78                 |
| Voltage                                 | V-Ah              | 24[2x12] - 105 GEL | 24[2x12] - 105 GEL | 24[2x12] - 105 GEL | 24[2x12] - 105 GEL | 24[2x12] - 105 GEL | 24[2x12] - 105 GEL | 24[2x12] - 105 GEL |
| Installed power                         | W                 | 1030               | 1230               | 1440               | 1440               | 1440               | 2380               | 1400               |
| Brush pressure                          | kg                | 18,5               | 18,5               | 30,5               | 31,5               | 31,5               | 13,6/18,6          | 15-37              |
| Squeegee width                          | mm                | 815                | 815                | 815                | 1010               | 1010               | 815                | 1010               |
| Max speed                               | km/h              | 3,5                | 4,5                | 4,5                | 4,5                | 4,5                | 4,5                | 4,5                |
| Weight                                  | kg                | 72                 | 80                 | 94                 | 93                 | 95                 | 100,2              | 95                 |
| Dimension (LxWxH)                       | mm                | 1230x587x960       | 1230x587x960       | 1210x680x960       | 1220x748x960       | 1260x893x960       | 1260x893x960       | 1220x748x1140      |

## STANDARD EQUIPMENT

### BRUSHES

|                                       | CT70 B55  | CT70 BT55 | CT70 BT60   | CT70 BT70   | CT70 BT85   | CT70 BT55 R | CT70 BT70 ECS |
|---------------------------------------|-----------|-----------|-------------|-------------|-------------|-------------|---------------|
| PPL SOFT                              | SPPV01505 | SPPV01505 | 2XSPPV01473 | 2xSPPV01472 | 2xSPPV01516 | -           | 2xSPPV01481   |
| CYLINDRICAL BRUSH - PPL SOFT Ø 0,3 mm | -         | -         | -           | -           | -           | SPPV01163   | -             |
| PAD HOLDER                            | -         | -         | -           | -           | -           | -           | 2xSPPV01268   |

### SQUEEGEE BLADES

|                   |                   |                   |                   |                    |                    |                   |                    |
|-------------------|-------------------|-------------------|-------------------|--------------------|--------------------|-------------------|--------------------|
| LATEX FRONT BLADE | MPVR08039 - 880mm | MPVR08039 - 880mm | MPVR08039 - 880mm | MPVR08040 - 1020mm | MPVR08040 - 1020mm | MPVR08039 - 880mm | MPVR08040 - 1020mm |
| LATEX REAR BLADE  | MPVR08035 - 900mm | MPVR08035 - 900mm | MPVR08035 - 900mm | MPVR08036 - 1020mm | MPVR08036 - 1020mm | MPVR08035 - 900mm | MPVR08036 - 1020mm |

## CONSUMABLES (Codes available on price list)

### BRUSHES



### CYLINDRICAL BRUSHES



### PADS/SUPER PADS



### SQUEEGEE BLADES



## OPTIONAL ACCESSORIES

CODE: KTRI01763  
CHEM DOSE KIT



CODE: MPVR05611  
SPLASH GUARD (FOR BT55)



CODE: KTRI01573  
DISCHARGE HOSE



CODE: KTRI01870  
SOLUTION TANK DRAIN AND LEVEL HOSE KIT



CODE: KTRI02257  
EXTERNAL SUCTION KIT



CODE: KTRI02274  
ACCESSORIES SUPPORT KIT



CODE: PRCH00578  
BIOSAN RAPIDE WT (30PCS/30DAYS)



## BATTERIES AND BATTERY CHARGERS

| BATTERIES                           | N° | CHARACTERISTICS   | DIMENSION   | RUNNING TIME | BATTERY CHARGERS  |
|-------------------------------------|----|-------------------|-------------|--------------|---|
| IPC gel battery<br>BAAC00105        | 2  | 12V 105 Ah [ C5 ] | 345x170x285 | 150 min      | On board battery charger 24V 10 Ah- KTRI01703<br>Stand alone high frequency BLS010 - BACA00133  |
| EXIDE gel battery<br>BAAC00024      | 2  | 12V 105 Ah [ C5 ] | 345x174x283 | 150 min      | On board battery charger 24V 10 Ah- KTRI01703<br>Stand alone high frequency BLS010 - BACA00133  |
| Acid tubular plate<br>BAAC00136     | 2  | 12V 85 Ah [ C5 ]  | 308x175x225 | 160 min      | On board battery charger 24V 10 Ah- KTRI01703<br>Stand alone high frequency BLS010 - BACA00133<br>Stand alone low frequency 24V 12 Ah BACA00060 |
| Dry charge flate plate<br>BAAC00009 | 2  | 12V 105 Ah [ C5 ] | 261x171x210 | 160 min      | On board battery charger 24V 10 Ah- KTRI01703<br>Stand alone high frequency BLS010 - BACA00133<br>Stand alone low frequency 24V 12 Ah BACA00060 |
| Acid tubular plate<br>BAAC00070     | 2  | 12V 118 Ah [ C5 ] | 345x170x285 | 160 min      | On board battery charger 24V 10 Ah- KTRI01703<br>Stand alone high frequency BLS010 - BACA00133<br>Stand alone low frequency 24V 12 Ah BACA00060 |

RECOMMENDED BATTERIES AND BATTERY CHARGER