



## HIGH-PRESSURE WASHERS - COLD WATER STATIONARY

# MLC-C

### PRESSURE

130÷210  
bar

### FLOW RATE

600÷1000  
l/h

### ABSORBED POWER

3÷6,7 kW

### EXCLUSIVE CHARACTERISTICS

- ▶ BY-PASS - BYP (BY-PASS MODELS)
- ▶ THERMOSTATIC VALVE - TSV (BY-PASS MODELS)
- ▶ DELAYED TOTAL STOP - DTS ("D" MODELS)
- ▶ MICRO LEAKAGE CONTROL - MLC ("D" MODELS)
- ▶ FLOODING PREVENTION SYSTEM - FPS ("D" MODELS)
- ▶ NOZZLE CLOGGED CONTROL - NCC ("D" MODELS)
- ▶ WORKING HOURS COUNTER - WHC ("D" MODELS)
- ▶ INTELLIGENT PROPORTIONAL SWITCH OFF - IPSF ("D" MODELS)



### MOST FREQUENTLY USE

#### AUTOMOTIVE



#### AGRICULTURE



#### CONSTRUCTION INDUSTRY



#### MUNICIPALITIES



#### DIY AND GARDENING



#### HEAVY INDUSTRY



### INNOVATIONS



G6000™  
CERAMIC  
TECH GUN



MSC™  
MULTIFUNCTION  
SAFETY  
CONTROL

### SPECS



EQUIPPED WITH A PAINTED METAL PLATE FOR WALL-MOUNTING



PUMP WITH BRASS HEAD AND THREE CERAMIC PISTONS ENSURING LONG-TERM LIFESPAN



PROFESSIONAL PRESSURE GAUGE ENSURING A CONSTANT CONTROL OF WORKING PRESSURE

## TECHNICAL DATA

	BY-PASS MODELS				DELAYED TOTAL STOP MODELS				
	MLC-C 1310P M	MLC-C 1813P T	MLC-C 1915P T	MLC-C 2117P T	MLC-C D1310P M	MLC-C D1813P T	MLC-C D1915P T	MLC-C D2117P T	
Code	PPEL40078	PPEL40080	PPEL40082	PPEL40084	PPEL40079	PPEL40081	PPEL40083	PPEL40085	
PERFORMANCE									
Operating pressure	bar/Mpa	30-130/3-13	30-180/3-18	30-190/3-19	30-210/3-21	30-130/3-13	30-180/3-18	30-190/3-19	30-210/3-21
Flow rate	l/h	600	800	900	1000	600	800	900	1000
Inlet water max. temperature	°C	50	50	50	50	50	50	50	50
Power supply	Ph-V-Hz/A	1-230-50/14,5	3-400-50/8,6	3-400-50/9,4	3-400-50/12	1-230-50/14,5	3-400-50/8,6	3-400-50/9,4	3-400-50/12
Absorbed power	kW	3	4,7	5	6,4	3	4,7	5	6,4
Motor pole/rpm		4-1400	2-2800	4-1400	4-1400	4-1400	2-2800	4-1400	4-1400
Remote control		BYP	BYP	BYP	BYP	DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/ brass/ceramic	lpc plunger/ brass/ceramic	lpc plunger/ brass/ceramic	lpc plunger/ brass/ceramic	lpc plunger/ brass/ceramic	lpc plunger/ brass/ceramic	lpc plunger/ brass/ceramic	lpc plunger/ brass/ceramic
Detergent tank	l	-	-	-	-	-	-	-	-
Detergent delivery		-	-	-	-	-	-	-	-
Dimension (LxWxH)	cm	34x47x61	35x48x61	36x50x61	31x52x61	34x47x61	35x48x61	36x50x61	37x52x61
Weight	kg	35	35	40	50	35	35	40	50

## STANDARD EQUIPMENT

CODE: IPPR40020  
HANDGRIP G6000



CODE: LCPR40087  
EXTENSION P70 INOX



CODE: UGLN40000  
H.P. NOZZLE 1/4  
UG.15034 (FOR 1310)



CODE: UGLN49987  
H.P. NOZZLE 1/4  
UG.15045  
(FOR 1813/1915/2117)



CODE: TBAP25324  
HIGH PRESSURE HOSE  
10 m



## OPTIONAL ACCESSORIES

CODE: IPIP40014  
GRIP G6000 BAYONET



CODE: LCLC40004  
EXTENSION P70 - INOX  
BAYONET



CODE: LCPR40039  
FOAMER KIT 1 l BAYONET  
(FOR IPIP40014)



CODE: LCPR40040  
FOAMER KIT M22 1 l  
(FOR IPPR40020)



CODE: LCPR14858  
SADBASTER KIT Ø 1,4  
(FOR 1310) TO USE WITH  
IPPR40020



CODE: LCPR14859  
SADBASTER KIT Ø 1,6  
(FOR 1813/1915) TO USE  
WITH IPPR40020



CODE: LCPR13557  
SADBASTER KIT Ø 1,5  
(FOR 2117) TO USE WITH  
IPPR40020



CODE: PRCH00065  
SAND BAG 50 Kg



CODE: LCPR93178  
TURBO LANCE TTR-16  
D.1,35 (FOR 1310/1915)  
TO USE WITH IPPR40020



CODE: LCPR40016  
TURBO LANCE TTR-16  
D.1,40 (FOR 1813) TO USE  
WITH IPPR40020



CODE: LCPR40054  
TURBO LANCE TPR-25  
D.1,30 (FOR 2117) TO USE  
WITH IPPR40020



CODE: KTRI40311  
MAINTENANCE KIT 500H  
(FOR 1310)



CODE: KTRI40317  
MAINTENANCE KIT 500H  
(FOR 1813)



CODE: KTRI40313  
MAINTENANCE KIT 500H  
(FOR 1915)



CODE: KTRI40338  
MAINTENANCE KIT 500H  
(FOR 2117)

