

EVERYTHING YOU LOVE ABOUT ATTACHPRO, Now with video recording, survey mode, and a higher temperature range.

KEY CAMERA SPECS

	Resolution	320 x 240	Seek
T	Field of View	57° x 42°	thermal
**	Durability	IP67 waterproof, 2 meter drop	
l	Detection	-4°F to 1,200°F (-20°C to 650°C)	thermal.com
	Imaging	Mixed Gain with SV1	
= D)	Flashlight	300 Lumen LED	The Corp

Designed with firefighters for firefighters, the AttackPRO[™] VRS is the latest addition to the AttackPRO Series.

AttackPRO VRS builds on the unmatched image quality, durability, and affordability of the original AttackPRO. It now features video recording, a higher temperature range up to 1,200°F, and includes Survey Mode to enhance size-up and overhaul operations.

With high-resolution, mixed-gain pixel technology, AttackPRO VRS ensures clear visibility of both fire and crew in one detailed image. The kit includes the camera, 2 batteries, and a charging dock.

Designed and Manufactured in the USA with Global Components. Thermal sensor designed and manufactured by Seek in Santa Barbara, CA USA





KEY FEATURES

Video Recording + 1,200°F Detection + Survey Mode Record up 5 hours of video on AttackPRO's 32GB internal drive

Mixed Gain with SV1 Image Optimization See the hottest and coolest regions of the scene simultaneously without freezing or switching gain modes; details enhanced with SV1

Durable, Waterproof Design Durable and reliable design built with IP67 rating and 2 meter drop resistance

Wide, 57-Degree Field of View Easily scan a large area to identify hazards or victims in seconds

Long-Lasting Rechargeable Battery Greater than 6 hours of continuous thermal imaging

BENEFITS

Decision Making on Command Direct Firefighters, water, and resources with expedited tactical precision

Robust Decision Making TIC Equip every commanding officer with the first affordable decision making TIC

300 Lumen Integrated Flashlight LED flashlight available at the touch of a button

Search and Rescue Find victims and self-rescue faster with a reliable personal TIC

Execute 360 Size-ups & Overhaul Faster When seconds count, a Seek decision-making TIC saves time and lives





TECHNICAL SUMMARY

SPECIFICATIONS	DESCRIPTION
Thermal Sensor	320 x 240 (76,800 pixels)
Detection Distance	12 inches to 1,000 feet
Field of View	57° HFOV, 42° VFOV
Temperature Range	-4 to 1,200°F (-20 to 650°C)
Operating Temp	-4 to 131°F (-20 to 55°C) - no time limit
	up to 302°F (150°C) - max 15 min
	up to 500F° (260°C) - max 5 min
Frame Rate	> 25 Hz Fast Frame
IP Rating	IP67 Waterproof
Flashlight	300 Lumen LED
Display	3.5" Color with Corning® Gorilla® Glass
Thermal Sensitivity	< 35 mK with SV1
User Interface	On device 2 tactile button operation
Temp. Display Scale	Fahrenheit or Celsius
Image modes	FIRE (TI Basic & TI Basic+) and SURVEY
Video Recording	5 Hours of video recording (32GB Internal drive)
Photo Capture	No
Battery	>6 Hours Thermal Imaging (w/o flashlight); >3hrs (with thermal AND flashlight)

300 LUMEN LED LIGHT



Seek AttackPRO VRS combines powerful thermal insight and a bright LED flashlight in an intuitive, two button interface.

MODES



TI BASIC

Maintain your situational awareness with a simple and decluttered display showing greyscale and colorized regions



TI BASIC+

Enhance your tactics with a spot temp readout while still maintaining greyscale and colorized regions




SURVEY MODE

Investigative mode with early colorization at 65C (150F) ideal for size up, smells & bells, and overhaul

For support and user guides visit thermal.com

THERMAL APPLICATIONS



360 SIZE UP



FIRE ATTACK



OVERHAUL



Seek more at thermal.com

6300 Hollister Ave, Santa Barbara, CA 93117

Seek Thermal engineers, designs and manufacturers high quality thermal imaging products and core platforms for consumer, commercial, and heat sensing IoT data applications. With headquarters in Santa Barbara, California, the global hub of thermal imaging innovation, the company has developed breakthrough thermal imaging camera cores that will enable a range of affordable products for use at home, work and play. For more information visit thermal.com and follow #seekthermal on Instagram and @seekthermal on Twitter.



DESKTOP BATTERY CHARGER

Seek thermal

SKU: FD-SAA



TECHNICAL SUMMARY

SPECIFICATIONS	DESCRIPTION
AC INPUT	100-240 VAC 50/60 HZ, 0.5 A
SUPPLY VOLTAGE	5VDC
POWER RATING	10W
ENVIRONMENTAL	INTENDED FOR INDOOR USE
CHARGE TIME	6 HOURS
INCLUDED IN THE BOX	DESKTOP CHARGER CRADLE POWER SUPPLY INCLUDING AC PLUGS FOR US, EU, UK

For support and user guides visit thermal.com

Seek more at thermal.com

6300 Hollister Ave, Santa Barbara, CA 93117

Seek Thermal engineers, designs and manufacturers high quality thermal imaging products and core platforms for consumer, commercial, and heat sensing IoT data applications. With headquarters in Santa Barbara, California, the global hub of thermal imaging innovation, the company has developed breakthrough thermal imaging camera cores that will enable a range of affordable products for use at home, work and play. For more information visit thermal.com and follow #seekthermal on Instagram and @seekthermal on Twitter.



BATTERY Li-ion , 3.63 V, 4.9 Ah, 17.79 Wh

SKU: FA-BAA



TECHNICAL SUMMARY

DESCRIPTION
LITHIUM ION
3.63 ∨
4900 mAh
DURING DISCHARGE: -20°C TO 60°C DURING CHARGING: 0°C TO 45°C
115g
170 X 45 X 43 mm
FQ-PPAX FQ-PPNX FQ-PAVX FQ-PPSX

For support and user guides visit thermal.com

Seek more at thermal.com

6300 Hollister Ave, Santa Barbara, CA 93117

Seek Thermal engineers, designs and manufacturers high quality thermal imaging products and core platforms for consumer, commercial, and heat sensing IoT data applications. With headquarters in Santa Barbara, California, the global hub of thermal imaging innovation, the company has developed breakthrough thermal imaging camera cores that will enable a range of affordable products for use at home, work and play. For more information visit thermal.com and follow #seekthermal on Instagram and @seekthermal on X.

