



Courant

AKA

- RIGGING ROPE -

DIAMETERS & COLOURS

- Ø 12mm
- Ø 14mm
- Ø 16mm
- Ø 18mm

LENGTH OPTIONS

40, 50, 60 meters

Master boxes	Ø 12mm	Ø 14mm	Ø 16mm	Ø 18mm
	1000m	900m	690m	470m

Other lengths available on request.

TERMINAISONS





1 splice
Without termination

KEY FEATURES




- Practical color coding
- Visible colors
- Wear-resistant
- Soft to the touch

The AKA rope collection is engineered for tree and other rigging applications. Its advanced core-sheath construction ensures seamless performance in rigging operations, enhancing operational efficiency. The rope's versatility is exemplified by its straightforward splicing capabilities in any configuration. A key feature is the precise twist regulation of each sheath strand, which maintains optimal stability and minimizes unwanted twisting during use.

TECHNICAL SPECIFICATIONS

	 Ø 12mm	 Ø 14mm	 Ø 16mm	 Ø 18mm
Materials / construction	Polyester	Polyester	Polyester	Polyester
Static resistance	3800 daN 8545 lbf	4800 daN 10791 lbf	5800 daN 13039 lbf	6800 daN 15287 lbf
Resistance with splice	3500 daN 7868 lbf	4500 daN 10116 lbf	5500 daN 12364 lbf	6500 daN 14613 lbf
Mass per meter	126 g/m	162 g/m	192 g/m	232 g/m
Sheath percentage	54%	54%	49%	46%
WLL	540 daN 1214 lbf	685 daN 1540 lbf	828 daN 1861 lbf	971 daN 2183 lbf
Référence	MHD++ABC+++	MXD++ALC+++	MYD++ACC+++	MZD++AGC+++



-  mycourant.com
-  couranttrecare
-  courant vertical living

