

<b>Universe</b>	Professional
<b>Type</b>	Verticality
<b>Category</b>	Ropes
<b>Subcategory</b>	Low stretch kernmantel ropes




## CONTROL 12.5 mm

The CONTROL 12.5 mm low stretch kernmantel rope is designed for tree care. The large diameter ensures high strength and excellent grip. The EverFlex technology guarantees great flexibility and handling over time. It comes with a splice at one end for optimal rope glide through devices like a friction saver or pulley, and through tree branches. The small size of the splice allows it to pass through the friction chain of the ZIGZAG and ZIGZAG PLUS mechanical Prusiks. Rope available in two colors and three lengths.



The rope's construction provides optimal performance when used with the ZIGZAG and ZIGZAG PLUS mechanical Prusiks.



EverFlex technology ensures great flexibility over time, which allows it to maintain excellent handling and optimal performance with devices.



The small size of the splice allows it to pass through the friction chain of the ZIGZAG and ZIGZAG PLUS mechanical Prusiks.

---

**Short Description** Low stretch kernmantel, high-strength rope with excellent handling, for tree care

---

**Selling Points**

- Designed for tree care: patented splice at one end for optimal rope glide through devices like a friction saver or pulley, and through tree branches. The small size of the splice allows it to pass through the friction chain of the ZIGZAG and ZIGZAG PLUS mechanical Prusiks.
- Large diameter ensures high strength and excellent grip
- Consistent performance over time:
  - 100% polyester double weave construction
  - EverFlex technology ensures great flexibility under any conditions (water, dust, mud...), allowing it to maintain excellent handling and optimal functioning with devices
- Available in two colors (green and orange), to help easily identify different working ropes
- Standard lengths: 35, 45 and 60 m





---



**Specification**

- Diameter: 12,5mm
- Material(s): polyester
- Certification(s): CE EN 1891 type A, ANSI Z133
- Weight per meter: 115g
- Strength tied with figure-eight knot: 15kN
- Strength with splice: 19kN
- Impact force (factor 0,3): 5,2kN
- Number of factor 1 falls: 8
- Construction: 24 carrier
- Percentage of sheath: 62%
- Static elongation: 3,1%

---

Specifications by reference

Reference(s)	R080AA00	R080AA01	R080AA02	R080AA03
				
Length	35 m	35 m	45 m	45 m
Color(s)	green	orange	green	orange
Made in	FR	FR	FR	FR
Guarantee	3 years	3 years	3 years	3 years
Packing	1	1	1	1
Case quantity	4	4	4	4
EAN	3342540829060	3342540829077	3342540829084	3342540829091

Reference(s)	R080AA04	R080AA05
		
Length	60 m	60 m
Color(s)	green	orange
Made in	FR	FR
Guarantee	3 years	3 years
Packing	1	1
Case quantity	2	2
EAN	3342540829107	3342540829213

---

**Accessory(ies)** TREESBEE  
TREESBEE SCREWLINK  
ROLLCLIP A  
ROLLCLIP Z

---

**Related product(s)** ZIGZAG®  
ZIGZAG® PLUS  
CHICANE