


Universe	Professional
Туре	Verticality
Category	Kits
Subcategory	Rescue kit




JAG RESCUE KIT

The JAG RESCUE KIT is a ready-to-use reversible rescue kit designed to easily pick off and lower a victim. It contains a JAG SYSTEM haul kit, a RING OPEN gated ring, an I'D EVAC descender with integrated brake, a CONNEXION FIXE 150 cm anchor strap, a BUCKET bag and an AXIS 11 mm rope with two sewn terminations. It is available in three lengths: 30, 60 and 120 m.



Hauling with the JAG SYSTEM haul kit whose 4:1 mechanical advantage and excellent sheave efficiency allow the user effort to be divided by four when raising a victim in order to release him.



Evacuation with the I'D EVAC descender, whose ergonomic handle allows the user to easily control the rope's descent speed during evacuation.

Short Description	Reversible rescue kit with JAG SYSTEM haul kit and I'D EVAC descender			
Selling Points	 Designed to easily pick off and lower a victim: pick-off with the JAG SYSTEM haul kit, whose 4:1 mechanical advantage and excellent sheave efficiency allow the user effort to be divided by 4 when raising a victim in order to release him evacuation with the I/D EVAC descender, whose handle is specially designed to easily lower a victim. Anti-panic function activates if the user pulls too hard on the handle, which brakes and stops the descent automatically Always ready to use for quick intervention: JAG SYSTEM equipped with flexible cover that prevents any risk of tangling rope is pre-installed in the closed brake, which is integrated in the descender to better control the descent and to provide a constant redirect BUCKET bag for transporting the kit kit comes loaded and ready to use Available in three rope length versions: 30, 60 and 120 meters Rescue kit contents: a JAG SYSTEM haul kit a RING OPEN gated ring an I'D EVAC descender an XIS 11 mm rope with two sewn terminations a CONNEXION FIXE 150 cm anchor strap 			
	- a BUCKET 25 liter bag for the 30 and 60 meter versions, and a 35 liter bag for the 120 meter version			
Specification	 Working load limit: 250 kg Material(s): aluminum, steel, nylon, polyurethane, polyester 			

Specifications by reference

Reference(s)	K090AA00	K090AA01	K090AA02
Length	30 m	60 m	120 m
Weight	4300 g	6600 g	11300 g
Made in	FR	FR	FR
Guarantee	3 years	3 years	3 years
Inner Pack Count	1	1	1
Quantity Per Box	1	1	1
EAN	3342540826618	3342540826601	3342540826588

