

Universe	Professional
Type	Verticality
Category	Pulleys
Subcategory	High-efficiency pulleys




PRO

Openable even when attached to the anchor, the PRO pulley is designed for maximum simplicity when setting up hauling or load deviation systems. The side plate that locks under load, the large-diameter sheave and the very high efficiency sealed ball bearings make a pulley that is well suited for handling heavy loads.



The rope may be installed even when the PRO pulley is connected to the anchor.



The pulley always stays attached to its connector, limiting the risk of losing the device.



The side plate locks under load to prevent opening of the pulley during use.

Short Description Very high-efficiency loss-resistant pulley

Selling Points

- Designed for maximum simplicity when setting up hauling or load deviation systems:
 - the rope can be easily installed even when the pulley is connected to the anchor
 - the pulley always stays attached to its connector, limiting the risk of losing the device
- Especially suited for handling heavy loads:
 - large diameter sheave mounted on sealed ball bearings for excellent efficiency
 - side plate locks when loaded and prevents opening of the pulley during use

Specification

- Weight: 205g
- Certification(s): CE EN 12278, EAC, NFPA 1983 Technical Use
- Material(s): aluminum, nylon
- Min. rope diameter: 7mm
- Max. rope diameter: 13mm
- Sheave type: sealed ball bearings
- Sheave diameter: 38mm
- Maximum working load: $2 \times 2,5 = 5\text{kN}$
- Breaking strength: $2 \times 11 = 22\text{kN}$
- Efficiency: 95%

Specifications by reference

Reference(s)	P46
Made in	FR
Guarantee	3 years
Inner pack count	1
Case quantity	8
EAN	3342540100374

Related product(s) OK
 SWIVEL OPEN