

| | |
|--------------------|-------------------|
| Universe | Professional |
| Type | Verticality |
| Category | Anchors |
| Subcategory | Rigging equipment |



RING OPEN Dark Grey

The RING OPEN gated ring is designed for semi-permanent connection of equipment. Its round shape provides optimal functioning in all directions. It has a large opening that allows installation of ropes with sewn terminations.



Wide opening allows installation of ropes with sewn terminations.

Short Description Multidirectional gated ring

Selling Points

- Ring designed for semi-permanent connection of equipment
- Round shape for optimal functioning in all directions
- Wide opening allows installation of ropes with sewn terminations

Specification

- Major axis strength: 23kN
- Minor axis strength: 23kN
- Opening: 11 mm
- Weight: 70g
- Certification(s): CE EN 362
- Material(s): Aluminum, plastic

Specifications by reference

| | |
|---------------------|-----------------|
| Reference(s) | M028AA00 |
| Made in | FR |
| Color(s) | Dark Grey |
| Guarantee | 3 years |
| Inner Pack Count | 1 |
| Quantity Per Box | 25 |
| EAN | 3342540839786 |

Related product(s) PROGRESS ADJUST-I Progression Lanyard
 PROGRESS ADJUST-Y
 ABSORBICA®