


<b>Universe</b>	Professional
<b>Type</b>	Verticality
<b>Category</b>	Pulleys
<b>Subcategory</b>	Pulley-carabiners




## ROLLCLIP A

ROLLCLIP A is a pulley-carabiner with a gate opening on the pulley side that facilitates installation of the rope when the pulley is fixed to the anchor. It is available with an automatic TRIACT-LOCK locking system, or without a locking system. ROLLCLIP A may be used with a CAPTIV positioning bar to favor loading of the carabiner along the major axis, to limit the risk of it flipping and to keep it integrated with the device.



The ROLLCLIP A pulley may be used as a directional point on the lower attachment point of the ASCENSION handled rope clamp, for short rope ascents. Gate opening on the pulley side facilitates installation of the rope.



The ROLLCLIP A pulley can be used as a directional point when combined with the RESCUCENDER rope clamp.

---



**Short Description** Pulley-carabiner that facilitates installation of the rope when pulley is connected to the anchor

---

- Selling Points**
- Easier handling:
    - sheave mounted on sealed ball bearings for excellent efficiency
    - gate opening on the pulley side facilitates installation of the rope when the pulley is fixed to the anchor
    - may be used with a CAPTIV positioning bar to favor loading of the carabiner along the major axis and to limit the risk of it flipping
    - Keylock system prevents any accidental snagging of the carabiner when putting the pulley in place
  - H cross-section of carabiner:
    - ensures an improved strength-to-weight ratio
    - protects markings from abrasion
  - Available in versions with or without TRIACT-LOCK locking system

- 
- Specification**
- Material(s): aluminum
  - Min. rope diameter: 7mm
  - Max. rope diameter: 13mm
  - Sheave diameter: 18mm
  - Maximum working load:  $2 \times 2 = 4\text{kN}$
  - Efficiency: 85%
  - Major axis strength: 20kN
  - Minor axis strength: 8kN
  - Open gate strength: 7kN
-

**Specifications by reference**

Reference(s)	P74 TL	P74
		
Locking system	TRIACT-LOCK	Non-locking
Weight	115 g	105 g
Certification(s)	CE EN 362, EN 12275, EN 12278, EAC	CE EN 12275, EN 12278, EAC
Gate opening	22 mm	25 mm
Made in	FR	FR
Guarantee	3 years	3 years
Inner Pack Count	1	1
Quantity Per Box	10	10
EAN	3342540104082	3342540103856

---

**Accessory(ies)**      CAPTIV