

SQUIR

ACCESS ROPE

CE EN1891-A

DIAMETER

Ø 11.5 mm

COLOUR OPTIONS

■ RED

■ YELLOW

LENGTH OPTIONS

Red:
60, 70, 200 & 900 meters

Yellow:
60, 70, 200 & 900 meters

(Other lengths available on request)

TERMINATION

None available

KEY FEATURES

- Very low stretch
- Superior wear resistance
- Heat treated for extra stability
- Exciting colour combinations
- Retains it's flexibility over time

Designed for SRT or use as an access line, the re-developed Squir has a more durable but very flexible polyester sheath. It's low stretch ensures that the bounce effect is kept to a minimum when climbing. Users admire the performance of the rope when combined with the latest metal friction devices on the market.

TECHNICAL SPECIFICATIONS



- Materials / construction: 32-strand Polyester sheath with X-Braid Polyamide core
- Static resistance: 30kN
- Resistance with figure of 8 knot: 21kN
- Mass per meter: 91gram
- Sheath percentage: 43%
- Sheath slippage: 0.2%
- Elongation 50/150Kg: 2%
- Knotability: 0.74
- Retraction with water: 1.5%
- Maximum lifespan: 10 years under normal working conditions

Reference: MJ100++++++

