



COLLABORATE Versa Pro 150 brings professional video and audio quality to all popular BYOD web-conferencing applications.

The solution addresses today's AV needs for mid-size meeting rooms with its DSP Mixer, Ceiling Mic Array and USB PTZ Camera.

CONVERGE® Huddle Mixer

- + Next-gen Acoustic Echo Cancellation processing
- + Distributed Echo Cancellation® on every mic input
- + Noise Cancellation with Adaptive-Ambience
- + Acoustic Intelligence with faster convergence

Ceiling Mic Array

- + Full 360-degree coverage
- + Three unidirectional mic elements
- + Design minimizes reverb and noise pickup from ceiling sources
- + RF hardened and shielded for immunity from interference

UNITE 150 USB PTZ camera

- + Full HD 1080p30
- + 12x optical zoom
- + 73° wide-angle
- + Backlight compensation

Bring-Your-Own Application

- + Compatible with all popular BYOD web-conferencing apps such as: Spontania®, Skype® for Business, Zoom, Webex, GoToMeeting, COLLABORATE Space, and more
- + In-room presentation



APPLICATIONS

BYOD Video Conferencing

BYOD Audio Conferencing

In-room Presentation

Huddle Spaces

Small Meeting Rooms

Mid-size Meeting Rooms

Executive Offices

Components



CONVERGE Huddle



Ceiling Microphone Array



UNITE 150
USB PTZ Camera

Note: Components not shown to scale.

Connection Diagram



PRODUCT SPECIFICATIONS

CONVERGE Huddle

Inputs:

3 channel balanced audio mic/line inputs with AEC
1 channel balanced audio line input without AEC
3.81mm orange-color Phoenix/Euroblock type male header, push-on mini-terminal block

Line Outputs:

2 channel balanced audio line outputs, 3.81mm black-color Phoenix/Euroblock type male header, push-on mini-terminal block
1 USB 3.0 Type-B
2 USB 3.0 Type-A
RJ-45, 10/100/1000Mbps, passthrough to USB-B 3.0

HDMI Resolutions:

1600 x 1200p @ 60Hz, 4:3 ratio
1920 x 1200p @ 60Hz, 16:10 ratio
2560 x 1440p @ 60Hz, 16:9 ratio

UNITE 150 PTZ Camera

Line Outputs:

Full HD 1080p30
12x optical zoom
73° wide-angle view
USB 3.0/2.0
Line In

Control:

Remote control, USB (UVC), RS-232

Pan/Tile Angles:

±170°, Tilt: -30° to +90°

Ceiling Microphone Array

Acoustic Characteristics:

Polar Pattern: Cardioid
Dynamic Range: 80 dB, 1 kHz @ max SPL
Signal/Noise Ratio: 60 dBA, 1kHz @ 1Pa
Frequency Response: 100 Hz - 12kHz
Sensitivity: 114 mV/Pa

Electrical Characteristics:

Element: Fixed-charge back plate permanently polarized condenser
Phantom Power Requirement: 12-52 vdc, 2 mA typical
Impedance: 200 Ω

Part Number

930-3200-150

Includes: CONVERGE Huddle
UNITE 150 USB PTZ Camera
Ceiling Mic Array (White)

SALES AND INQUIRIES

Headquarters

5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116

US & Canada

Tel: 801.975.7200
TollFree: 800.945.7730
Fax: 801.303.5711

International

Tel: +1.801.975.7200
global@clearone.com

Sales

Tel: 801.975.7200
sales@clearone.com

TechSupport

Tel: 801.974.3760
tech.support@clearone.com