



# ATDM-1012

## Digital SmartMixer



### Features

- High-quality mic/line inputs with discrete amplifiers and remotely controllable mic preamps.
- Up to two ES954 Hanging Microphone Arrays (sold separately) can be integrated with the mixer.
- Full-matrix mixer with flexible input/output assignments.
- USB audio I/O (1 stereo input and 1 stereo output).
- Acoustic Echo Cancellation (AEC) and Noise Cancelling (NC) for use with up to 10 mic inputs.
- Audio-Technica LINK support for cascading up to 8 ATDM devices.
- Dante-compatible model (ATDM-1012DAN) available.
- 1U design is 19" rack compatible.

### Specifications

<b>Dynamic range / S/N ratio</b>	110 dB or higher (A-weighted/ST) / 90 dB or higher (A-weighted/ST)
<b>Maximum input level</b>	MIC: -20 dBu LINE: +24 dBu ST: +20 dBV
<b>Maximum output level</b>	Output 1-8 (Balanced): +24 dBu / +20dBV / +10 dBV Output ST (Unbalanced): +20 dBV / +10 dBV / -13 dBV
<b>Maximum gain</b>	64 dB
<b>Input/output terminal</b>	MIC/LINE input 1-10: Euroblock 3 pin ST input 1/2: Euroblock 3 pin Output 1-8, ST output 1/2: Euroblock 3 pin
<b>USB port</b>	USB Type-B (Device): Stereo input x 1 ch, Stereo output x 1 ch (24-bit)
<b>LINK/CHAIN</b>	A/B/C/D terminal: RJ-45 x 4
<b>Network port (ATDM-1012DAN only)</b>	Network port: RJ-45 x 1 (Dante Primary/Secondary, Network port: RJ-45 x 2)
<b>Power supply</b>	100 to 240 V AC (50/60 Hz)
<b>Operating temperature range</b>	0 to 40°C (32 to 104° F)
<b>Dimensions</b>	482.6 mm (19") x 324.3 mm (12.77") x 44 mm (1.73") (W x D x H)
<b>Weight</b>	3.6 kg (7.9 lbs)
<b>Accessories</b>	<ul style="list-style-type: none"> <li>• Power cable</li> <li>• Euroblock connector x 22</li> </ul>

*For product improvement, the product is subject to modification without notice.*

