

Pana 21:9 Displays

Pana 105 Touch
Pana 105 Non-Touch

Pana 81 Touch
Pana 81 Non-Touch



Pana 21:9 Displays

- **21:9 in native 5K resolution**
- **Touch and Non-Touch versions**

See the World through a 21:9 Lens

Pana's 21:9 ultra-wide 5K resolution brings a refreshing form factor to the conventional display market. Our 8-foot wide Pana 105 canvas optimizes team productivity allowing for improved interaction and work place collaboration.

The market most receptive to this format are enterprise and industrial companies leaning into visualization technology to be their focal point and center piece. CIOs are telling us 21:9 is making the biggest impressions enabling them to stand out, land new clients and attract better talent. That's a win-win.

Lightweight and maneuverable, the Pana is ideal for retrofits as all sizes fit into a commercial service elevator and can be mounted using standard industry hardware without reinforced concrete or steel backing. Pana's lower infrastructure costs equates to a lower cost of ownership as a result of easy retrofit, reduced energy consumption and affordable price point. All Pana displays are Energy Star certified.

PANA FEATURES

21:9 Panoramic

The extra wide form factor is inspired by our natural human ability to see wider than we see taller.

5K Resolution

Pana provides 33% more pixels with 5K resolution giving the user more real estate in which to work.

Interactive User Experience

Touch enables the expectation for interactive autonomy, speed and ease-of-use. Pana interactive displays are touch driven by multiple, simultaneous collaborators.

Built for Human Interaction

More pertinent information gets placed in our visual sweet spot increasing our comprehension and productivity. And all the pixels are placed where everyone on the team can reach them preserving our dignity among our peers of not having to overreach or bend over to interact with the display.

Interactivity through SimpleShare®

Jupiter's proprietary SimpleShare software enables intuitive interaction optimized for Pana displays. The platform provides quick and easy access to your daily workflow.

Pana 21:9 Displays Specifications

| | Pana 105 Touch | Pana 105 Non-Touch | Pana 81 Touch | Pana 81 Non-Touch |
|--------------------------------------|---|--|---|---|
| SPECIFICATIONS | | | | |
| Model Name | Pana 105T | Pana 105D | Pana 81T | Pana 81D |
| Resolution | 5120 x 2160 | 5120 x 2160 | 5120 x 2160 | 5120 x 2160 |
| Orientation | Landscape or Portrait | Landscape or Portrait | Landscape or Portrait | Landscape or Portrait |
| Screen Size | 105" (2667mm) diagonal | 105" (2667mm) diagonal | 81" (2057mm) diagonal | 81" (2057mm) diagonal |
| Contrast Ratio | 4000:1 | 4000:1 | 4000:1 | 4000:1 |
| Brightness | 600 cd/m ² | 650 cd/m ² | 600 cd/m ² | 650 cd/m ² |
| Refresh Rate | 60Hz | 60Hz | 60Hz | 60Hz |
| Viewing Angle | 178° H/V | 178° H/V | 178° H/V | 178° H/V |
| Lifetime | ≥ 50,000 Hrs | ≥ 50,000 Hrs | ≥ 50,000 Hrs | ≥ 50,000 Hrs |
| Response Time | 8 ms | 8 ms | 8 ms | 8 ms |
| Display | 21:9 aspect ratio, anti-glare, IPS LCD with local dimming, direct-bonding IR with 20 simultaneous touch points | 21:9 aspect ratio, anti-glare, IPS LCD with local dimming | 21:9 aspect ratio, anti-glare, IPS LCD with local dimming, bezel-less metal-mesh capacitive with 20 simultaneous touch points | 21:9 aspect ratio, anti-glare, IPS LCD with local dimming |
| HDCP Support | 2.2 | 2.2 | 2.2 | 2.2 |
| POWER | | | | |
| Input Current | 100-240 VAC 60/50 Hz 6Amp | 100-240 VAC 60/50 Hz 6Amp | 100-240 VAC 60/50 Hz 6Amp | 100-240 VAC 60/50 Hz 6Amp |
| Power Standby | 0.5 W | 0.5 W | 0.5 W | 0.5 W |
| Internal Speaker Output | 2 x 15 W | 2 x 15 W | 2 x 15 W | 2 x 15 W |
| Typical Power Consumption | 333 W | 312 W | 298 W | 302 W |
| Max Power Consumption | 600 W | 600 W | 500 W | 500 W |
| USB-C PD Output | 65W | 65W | 65W | 65W |
| Operating Temperature | 32° - 104°F (0° - 40°C) | 32° - 104°F (0° - 40°C) | 32° - 104°F (0° - 40°C) | 32° - 104°F (0° - 40°C) |
| CONNECTIVITY | | | | |
| DisplayPort 1.4 In | 1 | 1 | 1 | 1 |
| DisplayPort 1.4 Out | 1 (MST) | 1 (MST) | 1 (MST) | 1 (MST) |
| HDMI 2.0 In | 2 | 1 | 2 | 1 |
| USB-C | 1 | 1 | 1 | 1 |
| USB 2.0 Type-A | 4 | 4 | 4 | 4 |
| 3.5mm Line Out | 1 | 1 | 1 | 1 |
| S/PDIF Optical Fiber | 1 | 1 | 1 | 1 |
| Ethernet/RS232 | 1 | 1 | 1 | 1 |
| OPS Slot | JAE TX-25A | JAE TX-25A | JAE TX-25A | JAE TX-25A |
| ACCESSORIES | | | | |
| Ships With | Pana user manual, power cable, remote control & batteries | Pana user manual, power cable, remote control & batteries | Pana user manual, power cable, remote control & batteries | Pana user manual, power cable, remote control & batteries |
| Pana OPS (Optional) | i7, 16GB DDR4, 256GB (NVME), LAN, Wi-Fi, Bluetooth, Type-C. | i7, 16GB DDR4, 256GB (NVME), LAN, Wi-Fi, Bluetooth, Type-C. | i7, 16GB DDR4, 256GB (NVME), LAN, Wi-Fi, Bluetooth, Type-C. | i7, 16GB DDR4, 256GB (NVME), LAN, Wi-Fi, Bluetooth, Type-C. |
| Pana Pen (Optional) | Active Smart Pen, Pen & Windows Ink support. | | Active Smart Pen, Pen & Windows Ink support. | |
| DIMENSIONS | | | | |
| Dimensions | 99.2" x 43.5" x 4.3" (2520mm x 1105mm x 109mm) | 96.5" x 40.7" x 3.7" (2450mm x 1034mm x 94mm) | 76.1" x 33.3" x 3.4" (1933mm x 847mm x 86mm) | 75.6" x 32.7" x 3.3" (1919mm x 830mm x 83mm) |
| Weight | 207 lbs (94 kg) | 135.5 lbs (61.5 kg) | 117 lbs (53 kg) | 77 lbs (35 kg) |
| Shipping Dimensions | 109.4" x 59" x 13" (2780mm x 1500mm x 330mm) | 105.5" x 55.1" x 12.6" (2680mm x 1400mm x 320mm) | 84.4" x 40.0" x 10.3" (2145mm x 1015mm x 262mm) | 84.4" x 40.0" x 10.3" (2145mm x 1015mm x 262mm) |
| Shipping Weight | 258 lbs (117 kg) | 192 lbs (87 kg) | 141 lbs (64 kg) | 105 lbs (47 kg) |
| Mount Dimensions | 1500mm x 600mm | 1500mm x 600mm | 800mm x 400mm | 800mm x 400mm |
| CERTIFICATIONS | | | | |
| Regulatory and Safety Certifications | cULus, FCC, RoHS, Energy Star, CEC, CA65, CE, ErP, REACH, WEEE, UKCA, IECEE, SAA, RCM, GEMS, PSE, VCCI, PSB, CCC, INMETRO, NOM, BIS | cULus, FCC, RoHS, Energy Star, CEC, CA65, CE, ErP, REACH, WEEE, UKCA, IECEE, SAA, RCM, GEMS, PSE, VCCI, PSB, CCC, INMETRO, NOM, BIS, Display HDR 400 | cULus, FCC, RoHS, CEC, CA65, CE, ErP, REACH, WEEE, UKCA, IECEE, SAA, RCM, GEMS, PSE, VCCI, PSB, CCC, INMETRO, NOM, BIS | cULus, FCC, RoHS, Energy Star, CEC, CA65, CE, ErP, REACH, WEEE, UKCA, IECEE, SAA, RCM, GEMS, PSE, VCCI, PSB, CCC, INMETRO, NOM, BIS |

Pana 105 shown in Landscape and Portrait orientation.



jupiter.com

© 2021 Jupiter. Jupiter is a registered trademark of Jupiter Systems, Inc. Product specifications and designs are subject to change without notice. All brand and product names and logos are registered trademarks of Jupiter Systems, Inc.

DS_PANA_MAY2022