

# BASSO112

12" ultra-high power infra-subwoofer

## Highlights:

---

- 2000 Watt program power
- Low frequency extension down to 26Hz without processing
- 124 dB of Max SPL (continuous)
- Indoor model with Polyurea coated 18/36mm multiply plywood
- Extremely ridged chassis and inner framing

## Product information:

---

Engineered for demanding environments such as nightclubs, concert venues, theme parks, and hospitality spaces, the BASSO Series combines cutting-edge technologies like the pure carbon fiber cone and AeroVent for exponential low-noise venting with meticulous craftsmanship to set a new standard in low-frequency fidelity.

With a focus on ultra-high power output and exceptional sound clarity, the BASSO Series offers a flexible, efficient solution for diverse applications. Each model is designed to deliver a visceral sound experience with immersive infra-sub performance and extremely low distortion.

## Applications:

---

- Bars & Restaurants
- Hotels
- Clubs
- Sporting facilities
- Events
- Concert venues
- Museums & Themeparks



## Impedance:

---

$\Omega$  8 Ohm

## Usage:

---



Indoor

System specifications:

Speaker type		12" Infra-Sub
Configuration		AeroVent
Peak power handling		4000 W
Program power handling		2000 W
Continuous power (AES)		1000 W
Impedance		8 Ω
Max SPL (Continuous)		124 dB
Sensitivity (1W/1m)		94 dB
Frequency	Response (- 3 dB)	33 Hz - 120 Hz
	Range (-10 dB)	26 Hz - 200 Hz
Bass port tuning frequency		39 Hz
Drivers		12" carbon cone with dual suspension (low-loss) and 3.5" high excursion voice coil
Connectors		High-current terminal block with linkthrough

Product Features:

Dimensions		608 x 366 x 595 mm (W x H x D) (excluding feet)
		608 x 371 x 595 mm (W x H x D) (including feet)
Weight		26 kg
Operating temperature		-20 °C ~ 70 °C
Construction		18 mm Multiply plywood
		Coating - Multi-Layer polyurea coating (4-layer)
		Metal parts - Zinc plated bolts & fasteners
Front finish		2.0 mm Zinc plated steel with hexagon perforations and powder coat & acoustical foam backing
Mounting & handling	Rigging points	8 x M10 mounting bracket installation holes on both sides
	Stand fitting	1 x M20 internal thread stand adapter
Colours		Black

Variants:

- BASSO112/B - Black version