



Model	SE-2200VDA	SE-4200VDA	SE-8200VDA
Type	class D	class D	class D
8ohm Output Power	2x200W	4x200W	8x200W
4ohm Output Power	2x380W	4x380W	8x380W
2ohm Output Power	2x600W	4x600W	8x600W
8ohm Bridge	760W	2x760W	4x760W
Frequency Range	10Hz-20kHz	10Hz-20kHz	10Hz-20kHz
THD 1kHz	0,05%	0,05%	0,05%
S/N	100dB	100dB	100dB
Damping factor	>600	>600	>600
Crosstalk	>70dB	>70dB	>70dB
Input sensitivity	0,775V/1,4V/2,8V	0,775/1,2V	0,775V/1,2V
Input impedance	10kohm	10kohm	10kohm
Front panel LED	Signal/clip/protect	Signal/clip/protect	Signal/clip/protect
Rear panel control	Bridge/Parallell/Sens	Bridge/Parallell/Sens	Bridge/Parallell/Sens
Input Connector	XLR / RCA	Phoenix plug	Phoenix plug
Output Connector	2x Speakon	4xSpeakon	4xSpeakon
Cooling	2 fan variabel speed	2 fan variabel speed	2 fan variabel speed
Dimensions	483x295x44mm	483x320x44mm	483x420x88
Weight	6kg	7kg	8kg