



Model	SE-2390VDA	SE-4390VDA	SE-8390VDA
Type	class D	class D	class D
8ohm Output Power	2x390W	4x390	8x390W
4ohm Output Power	2x750W	4x750W	8x750W
2ohm Output Power	2x1200W	4x1200W	8x1200W
8ohm Bridge	1400W	1400W	1400W
Frequency Range	10Hz-20kHz	10Hz-20kHz	10Hz-20kHz
THD 1kHz	0,05%	0,05%	0,05%
S/N	100dB	100dB	100dB
Damping factor	>600	>600	>600
Crosstalk	>70dB	>70dB	>70dB
Input sensitivity	0,775/1,4/2,8V	0,775/1,2V	0,775/1,2V
Input impedance	10kohm	10kohm	10kohm
Front panel LED	Signal/clip/protect	Signal/clip/protect	Signal/clip/protect
Rear panel control	Bridge/Parallell/Sens	Bridge/Parallell/Sens	Bridge/Parallell/Sens
Input Connector	XLR/Rca	Phoenix plug	Phoenix plug
Output Connector	2xSpeakon	4xSpeakon	4xSpeakon 1+1-/2+2-
Cooling	2 fan variabel speed	2 fan variabel speed	2 fan variabel speed
Dimensions	483x295x44mm	483x320x44mm	483x420x44mm
Weight	6kg	7kg	8kg