

SMS CASING PROTECT SHADOW WALL



Casing Protect Shadow

Our most advanced outdoor system for digital signage yet. Choose your placement and colour to match your brand or the environment.

Vandal and IP55 Protected

Unbreakable Hammerglass™ together with the powder coated aluminum body, quadruple compression locks, rubber seals, water mazes and filters protect the solution against vandalism, water and dust from all directions.

User focused design

Hinged door with gas springs allows easy access to filters, fans and heaters. Aluminum as main material minimizes the total weight for the system, making installation and maintenance easier.

Temperature-controlled system

Highly sensitive sensors placed in the middle of the system with active thermostats ensure a well-controlled environment and protection of the display by sending signals to the heating and cooling system.

Adaptive installation

Select your preferred coloring and choose between the wall mounted or the freestanding version to fulfill your needs.

ARTICLE NUMBER

K704-001-13

55P Casing Shadow Wall G3 BL

DESCRIPTION

Placement: To be placed away from direct sunlight
Max display dimensions: 1300 x 740 x 70 mm. W x H x D, up to 750cd/m²

INCLUDED PRODUCTS

55P Protect Shadow Wall Mount BL

1 x 704-002-1

55P Protect Shadow Body G3 BL

1 x 704-001-13

INFO

PLACEMENT	Wall
ROTATION	Portrait
SCREEN BRIGHTNESS	750cd/m ²
OPERATION BRIGHTNESS	To be placed away from direct sunlight
OPERATION TEMPERATURE	-30C to +35C
OPERATION HUMIDITY	20% to 80%
POWER SUPPLY	85VAC to 265VAC, 10A fuse
POWER CONSUMPTION	1120W
LOCKABLE	Yes
PROTECTION GLASS SPEC	Polycarbonate
WATER PROTECTED IP GRADE	5
DUST PROTECTED IP GRADE	5
FANS SPEC	4x 12W axial fans
HEATERS SPEC	2x 200W
CERTIFICATES SPEC	CE
VESA HORIZONTAL	200 - 600
VESA VERTICAL	300 - 600
FITS MAX DIMENSIONS [MM]	L: 1300, H: 740, D: 70
SCREEN SIZE	55"
WARRANTY [YEARS]	2 years

PRODUCT VARIATIONS

K704-001-13 - 55P CASING SHADOW WALL G3 BL

Placement: To be placed away from direct sunlight Max display dimensions: 1300 x 740 x 70 mm. W x H x D, up to 750cd/m²

K704-001-23 - 55P CASING SHADOW WALL G3 DG

Placement: To be placed away from direct sunlight Max display dimensions: 1300 x 740 x 70 mm. W x H x D, up to 750cd/m²

K704-001-43 - 55P CASING SHADOW WALL G3 WH

Placement: To be placed away from direct sunlight Max display dimensions: 1300 x 740 x 70 mm. W x H x D, up to 750cd/m²