

Key Features

Extended Lifespan | Automatic

Sleep Timer | Auto Power Off |

Bright Images in Any Environment |


Amazing Colour Accuracy



Product **Description**

The ViewSonic PA503W offers impressive visual performance in small business meeting rooms and classrooms. With higher brightness and longer lamp life, PA503W projector is guaranteed to reproduce the finest of details in any environment for much longer. ViewSonic exclusive SuperColour™ technology offers a wider range of displayable colour ensuring true-to-life colour accuracy in both bright and dark environments without sacrificing image quality.





^{8.} Audio in/out

^{13.} Video

^{14.} Kensington® Lock Slot

Visit Us • www.viewsonic.com

SPECIFICATION		OTHERS	
Projection system:	0.65" WXGA	Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Native Resolution:	1280x800		
DC type:	DC3	Power Consumption:	Normal: 260W Standby: <0.5W
Brightness:	3600 ANSI Lumens	Operating Temperature:	0~40°C
Contrast Ratio with SuperEco	22000:1	Carton:	Brown
mode:		Net Weight:	2.2kg
Display Colour:	1.07 Billion Colours	Dimensions (WxDxH) w/adjustment foot:	294x218x110mm
Light Source:	Lamp	w/aujustinent 100t.	English Franch
Light source life (Nor/SuperEco):	5000/15000	Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese,
Lamp Watt:	200W		
Lens:	F=2.56-2.68, f=22-24.1 mm		
Projection Offset:	100%+/-5%		
Throw Ratio:	1.55~1.70		Japanese, Turkish,
Image size:	30" - 300"		Portuguese, Finnish,
Throw Distance:	1m-10.98m (100" @3.34m)		Indonesian, India, Arabic, Vietnamese
Keystone:	±40° (Vertical)	STANDARD ACCESSORY	
Optical Zoom:	1.1x	Power Cord:	1
Audible Noise (Eco):	27dB	VGA cable:	1
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)	Remote Control:	1
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	QSG & CD: Air Filter:	QSG: 1 / CD: NA RSPL
Video Compatibility:	NTSC, PAL, SECAM		
Horizontal Frequency:	15K~102KHz		
Vertical Scan Rate:	23~120Hz		
INPUT			
Computer in (D-SUB 15 pin):	2		
Composite:	1		
Audio-in (3.5mm):	1		
HDMI:	1 (Back)		
OUTPUT			
Monitor out (D-SUB 15 pin):	1		
Audio out (3.5mm):	1		
Speaker:	2W		

Copyright © ViewSonic Corporation 2000-2019. All rights reserved. (02/20/2019 07:55:34 America/Chicago)

CONTROL RS232:

USB type mini B (Services):