

[Doku typ](#) 02. Spezifikationen
[Brand](#) Bang & Olufsen
[Device](#) Lautsprecher
[Chassis](#)

[Typ](#) Beolab2
[Fault](#)
[TI Number](#)

[usable by](#)
[Sales date](#) 2001 - 2004
 (genauere Angabe über Jahrgang und UVP Preis finden Sie in unserer Web Preilliste)

[Info File](#)
[File-Infos](#)

Information



Market, Intro year and Last sold:

<u>Market:</u>	<u>Type:</u>	<u>Intro. year:</u>	<u>Last sold:</u>
EU	6861	06-2001	
GB	6862	06-2001	
USA-CDN-TWN	6863	06-2001	
J	6864	08-2001	
AUS	6865	06-2001	
KOR	6867	08-2001	

Specifications:

Dimensions	Height 315 mm Widht 260mm Depth 310mm Weight 17,7 kg
Cabinet finish	Aluminium, structure painted, grey
Power Consumption	Typical: 15 watts IEC65: 62W Stand-by: 0.4 watts
Maximum Sound Pressure Level	110 dB (stereo)
Power amplifier module	1 unit Class D
Long-term maximum output power	850 watts
Effective Frequency range*	23 - 120 Hz (upper limit determined by setup)
Cabinet principle	Double balanced passive radiator system
Magnetically shielded	Yes
Woofers	1 x 9" (250 mm) flat diaphragm

Passive radiator	2 x 9" (250 mm) flat diaphragm
Net volume	13 litres
Bass equalization	ABL (Adaptive Bass Linearization),
Switch for loudspeaker position	Free, Wall or Corner.
Input sensitivity	Adjustable by three position switch. Corresponding to -7 dB (3), 0 dB (2) or +3 dB (1) for main speakers.

* According to IEC 268-3 and 268-5.

Connections:

Power Link - Input	1
Power Link - Output	2
Mains	1

Market specifications:

<u>Type</u>	<u>Market</u>	<u>Voltage</u>
6861	EU	230 V
6862	GB	230 V
6863	USA - CND - TWN	120 V
6864	J	100 V
6865	AUS	240 V
6867	KOR	220 V