



# CH pro eco FORCE

## 30 / 38 / 45

Two motor basic carpet cleaner

### STRENGTHS

- › Strong and reliable
- › Only the essential accessories on board
- › Double support body / base
- › Balanced roller and metal supports with bearings
- › Hepa filter (optional)
- › Blowing function (optional)
- › 3 bases with the same suction body
- › Energy consumption combined: class "B"



eco FORCE



TECHNICAL DATA	30	CH pro eco FORCE 38	45
Input power (W)	850	880	900
Water lift mm/H <sub>2</sub> O (in/ H <sub>2</sub> O)	2300 (90)	2300 (90)	2300 (90)
Air volume lt/sec (CFM)	49 (103.8)	49 (103.8)	49 (103.8)
Motor protection	Termo/amp.	Termo/amp.	Termo/amp.
Two ply paper bag (lt.)	4	4	4
Washable TNT bag and Micropore	Optional	Optional	Optional
Exhaust Microfilter 3M Filtrete	Standard	Standard	Standard
Hepa filter H11	Optional	Optional	Optional
Cogged drive belt	Standard	Standard	Standard
Electronic overload control	Standard	Standard	Standard
Center convergent bristles brush (RPM)	5000	5000	4500
Working capacity m <sup>2</sup> /H (sq.ft/H)	480 (5100)	630 (6700)	750 (8000)
Sound power (db)	79	79	79
Total weight Kg (lb)	7,45 (16.4)	7,60 (16.7)	8,10 (17.8)
Cord lenght mt. (ft.)	10 (41)	10 (41)	10 (41)
Energy consumption combined (Class)	B	B	B

1. The machine comes down completely horizontally for easy access under low furniture and beds. The non positive latch system prevents from accidental breaking due to non pushing of the release pedal.
2. The electronic overload control switches off the motor in case of excessive overload and provides guidelines for the proper adjustment of the base.
3. The blowing function (optional) makes it possible to dislodge the most difficult dust.
4. Thanks to the stretch hose and the telescopic wand on board, is possible to connect the M28R hard floor tool.

