



FULL RANGE | BEST PERFORMANCE | ALL-ROUND

iT 6K400 LCD

A COMBINATION OF HIGH END AND UNIQUE BENEFITS

- Power level setting (kw)
- Multiple system temperature indicators (C°/F)
- User friendly LCD panel with 5 heat output levels (Keyboard upon request)
- Long inductor cable (3.0 m)
- **Plug and Play**



ART - iT 6K400 LCD

CUSTOMIZATION ON REQUEST

The iT 6K400 LCD heat inductors are ideal for a wide range of applications such as:

- Bolts/nuts releasing
- Pin or bearing release and replacement
- Heating for straightening
- Pre-heating before welding
- Bending
- Removing suspensions, shock absorbers, exhaust mufflers
- Straightening drive shafts

tecnical features



400x340x1000h mm



800x850x1280h mm



66 KG



Input power 6 Kw - 16 A Electrical connection IEC60309



400V/3PH+T 50





Working frequency 15-30 Khz



Duty cycle 30 min* (* ± 5% based on 20°C room temperature @ max power)



■ 8 m Network cable



P IP 21 Degree of protection



→ Main circuit breaker



20lt tank - Liquid cooling system



Hydraulic heat exchanger with fan



Directives and Certification



Plug & play with this IND 5KW/S03 flow concentrator