

Rail drilling machine

RAIL.40S

Available in 6 different rail adapter versions:
S49, S54, TRC68, UIC50, UIC54 and UIC60.

Technical data

| | Metric | Imperial |
|------------------------------|---|-------------------|
| Annular cutting | Ø 12 - 36 mm | Ø 7/16" - 1 7/16" |
| Length | 230 mm | 9 1/16" |
| Width | 180 mm | 7 1/16" |
| Height | 495 - 610 mm | 19 1/2" - 24" |
| Stroke | 155 mm | 6 1/8" |
| Weight* | 12 kg | 26.5 lbs |
| Motor power | 1,150 W | 10.5 A |
| Total power | 1,200 W | 10.9 A |
| Speed (no load) | 600 rpm | |
| Speed (load 1,150 W, 10.5 A) | 380 rpm | |
| Spindle (Weldon) | 19.05 mm | 3/4" |
| Voltage | 110 - 120 V / 60 Hz 220 - 240 V / 50 - 60 Hz | |

* Without power cord and handles



Features:



Oil lubricated
gearbox

Benefits:

- Suitable for processing rails
- High-efficiency motor with less heat generation
- High-accuracy capstan hub
- Direct spindle drive
- Integrated slide and one-speed oil lubricated gearbox for:
 - High accuracy
 - Enlarged lifecycle
 - Minimal vibration
- High-precision height adjustment for:
 - Low maintenance
 - Minimal wear correction