

Beveling machine

B60

Key specifications

Weight



24,1 kg

53.1 lbs

Motor



1100 W

10.0 A

Depth




24 mm max

15/16" max



Technical data

	Metric	Imperial
Spindle speed	2850 min ⁻¹	2850 rpm
Max. bevel depth	24 mm (45° angle)	15/16" (45° angle)
Bevel angle	0 - 60°	0 - 60°
Pipe diameter	150 - 300 mm	5 15/16" - 11 13/16"
Length	415 mm	16 5/16"
Width	375 mm	14 3/4"
Height	268 mm	10 9/16"
Weight	24,1 kg	53.1 lbs
Motor power	1100 W	10.0 A
Power supply	110 - 120 V AC / 50-60 Hz	220 - 240 V AC / 50-60 Hz



Cutting plates
10 pieces installed
(art.no. LKS.15)

Additional benefits:

- Powerful high efficiency motor
- Ultra-smooth operation with clear, precise and simple (protected) controls
- Clear indicator for angle-setting
- Suitable for both plate and pipe material
- Easy replacement and indexing of inserts
- Wide and soft handles



Clear markings



24 mm max.
bevel depth (at 45°)



Intertek



Intertek



Intertek

B601808.EN

EUROBOOR
FOR PROFESSIONALS BY PROFESSIONALS

Euroboor BV, Kryptonstraat 110, 2718 TD Zoetermeer The Netherlands - t +31(0)79 361 49 90 - info@euroboor.com - www.euroboor.com
magnetic drilling machines - annular cutters - beveling tools - tapping tools - sawing tools - grinding tools - accessories