

## FUEL INJECTION SYSTEM

**Tester for testing petrol and diesel fuel injectors  
(400 bar)**

item number: 041255  
Description: DET 06



### DESCRIPTION

- For the quick, easy and safe testing of injection nozzles / injectors of gasoline and diesel engines
- The following is checked:
  - opening pressure,
  - spray pattern,
  - tightness and
  - humming
- Measurement range 0 ... 400 bar / 0 ... 5800 psi
- Made from aluminium with reversible pump lever
- Enables easy and ergonomic pumping from above or from the front
- Liquid container (800 cm<sup>3</sup>) with plexiglass splash guard
- Displacement 35 cm<sup>3</sup>
- Precision pressure gauge NG 100, with rubber protection cap and double scale bar/psi
- All individual parts are available as spare parts

Note: Also available with drag pointer – DET 061

### SCOPE OF DELIVERY

- 1 injection tester
- 1 pressure line thread M 12x1.5
- 1 adapter DETA thread M 14x1.5

---

## EQUIPMENT

- DETA 01 (041254) Opel, motortype DTL + DTH (M 17x0,75 with closed cone);
- DETA 02 (041256) VW/Audi, motortype TDI (M 12x1.25)

---

## SPARE PARTS

- ET 462 (121492\_1) gauge DS 100, range 0...400 bar / 5800 psi (DET 06)
- ET 505 (121547) pump lever
- ET 506 (121548) strainer