




TECHNOLOGY 236 XT 230V ACX+ALU CASE



Overview

TECHNOLOGY 236 XT 230V ACX+ALU CASE

cod. 816251

MMA and TIG inverter, electrode welding machine in direct current (DC) with scratch striking.

Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron, etc.

Robust and impact resistant.

Features:

- compact and light
- 50 Ø dinse
- high welding current stability in spite of mains voltage fluctuations
- arc force, hot start and anti-stick devices
- thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections.

Complete with MMA welding accessories and aluminium carry case.



MMA TIG DC SCRATCH



CE MARKING



EAC CERTIFICATION



1 PH 230V

Technical data

CODE	CODE 816251	A_{MAX}	MAX ABSORBED CURRENT 38 A	φ	POWER FACTOR (cosphi) 0,7
V_{1PH}	SINGLE PHASE MAINS VOLTAGE 230 V	A_{60% MAX}	ABSORBED CURRENT AT 60% - MAX 22 A	Ø_{DC MIN/MAX}	D. USABLE ELECTRODES IN DC 1,6 - 4 mm
F	MAINS FREQUENCY 50 / 60 Hz	P_{MAX}	MAX ABSORBED POWER 6 kW	IP	PROTECTION DEGREE IP23
A_{MIN MAX}	CURRENT RANGE 5 - 200 A	P_{60%}	ABSORBED POWER AT 60% 3,3 kW	W_H L	DIMENSIONS 37,5 - 50 - 22 cm



TECHNOLOGY 236 XT 230V ACX+ALU CASE



MAX CURRENT 200 A - 35 %



MOTORGENERATOR MINIMUM POWER
10 kW



WEIGHT 10,55 kg



CURRENT AT 60% 140 A



EFFICIENCY 89 %



EAN CODE 800489716578 3



MAX NO LOAD VOLTAGE 60 V

Included Accessories

CABLE - 124887



TOLEDO 300 WORK CLAMP - 712231

CABLE TW05V-A 1X025 L=02.00M DINSE - 125033



DALLAS 300 ELECTRODE HOLDER 300A - 712260