

# Thermoforming technique Units

## Drufosmart scan

Pressure forming unit with integrated bar code scanner to identify blank codes and a working pressure of up to 4 bar. Display with self-explanatory control panel, vertical blank impression for best results. Due to the 2-hand operation and automatic switch-off function of the heating element safe working conditions are ensured. Covers the entire scope of thermoforming technology.



### Content:

from diameter 120 mm

- Base range of blanks
- Air connection hose (1 m)

red	D3400
silver	D34001



## Drufosmart

Basic pressure thermoforming unit with 2.5 bar working pressure. The better alternative in comparison to vacuum units with about three times higher forming pressure. Semi-automatic operation for easy adjustment of the corresponding heating times 2-hand operation and automatic switch off function of the heating element ensure safe working conditions.





### Content:

from diameter 120 mm

- Base range of blanks
- Air connection hose (1 m)

red	220–240 V / 50 Hz	D3200
red	115 V / 60 Hz	D3200A
silver	220–240 V / 50 Hz	D32001
silver	115 V / 60 Hz	D32001A



					
<b>Drufomat scan</b>	115–240 V / 50–60 Hz	max. 315 W	2–6 bar (19–87 psi)	16 kg	490x290x290 mm
<b>Drufosmart scan</b>	115–240 V / 50–60 Hz	max. 275 W	2–4 bar (19–58 psi)	15 kg	420x320x290 mm
<b>Drufosmart</b>	220–240 V / 50 Hz 115 V / 60 Hz	max. 275 W	2.5 bar (36 psi)	15 kg	420x320x290 mm