

# SIMPLA

## UNIVERSAL SINGLE-SIDED TAPE

- Versatile tape, it guarantees a progress adhesion, stable over time, for the most common supports
- Ideal for prefabrication, thanks to the special type of adhesive and the wide range
- Thanks to the type and amount of adhesive used, it is a perfect solution even at high temperatures



CODE	liner [mm]	B [mm]	L [m]	pcs
SIMPLA50	50	50	25	12
SIMPLA60	60	60	25	10
SIMPLA100	100	100	25	6

Thickness: 0,28 mm

## COMPOSITION

- ① support: PE film
- ② glue: acrylic dispersion without solvents
- ③ reinforcing layer: polyester reinforcing grid
- ④ glue: acrylic dispersion without solvents
- ⑤ release liner: silicone paper

## TECHNICAL DATA

properties	standard	value
thickness	-	0,28 mm
adhesiveness	EN 1939	≥ 35 N/25 mm
water vapour transmission (Sd)	EN ISO 12572	40 m
UV resistance	-	4 months
application temperature	-	-10 / +100 °C
thermal resistance	-	-40 / +100 °C
storage temperature <sup>(1)</sup>	-	+15 / +25 °C
solvents	-	no
VOC emissions	EN 16516	55 µg/m <sup>3</sup>
French VOC classification	ISO 16000	A+
EMICODE	GEV test procedure	EC1 <sup>PLUS</sup>

<sup>(1)</sup>Store the product in a dry, covered location.

