

Printing date 15.03.2021 Revision: 15.03.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Matt Black

· Article number: 443

· UFI: MDQX-S3WQ-D00U-8H0A

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

· Application of the substance / the mixture Coating compound/ Surface coating/ paint

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

RJP Panel & Paint Supplies Ltd

PO Box 251

Unit 1, 72 Williams Street

Kaiapoi

Christchurch 7630

· Further information obtainable from:

(03) 3755040

www.rjp.co.nz

· 1.4 Emergency telephone number: 0800 CHEMCALL (0800 243 622)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Acute Tox. 4 H332 Harmful if inhaled. Eve Irrit. 2 H319 Causes serious ev

Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms GHS02, GHS07
- · Signal word Danger
- Hazard-determining components of labelling:

propan-2-one

xylene

2-butoxyethanol

(Contd. on page 2)



Printing date 15.03.2021 Revision: 15.03.2021

Trade name: Matt Black

(Contd. of page 1)

1,2,4-trimethylbenzene

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 012119471330-49-0000	propan-2-one Flam. Liq. 2, H225 Acute Tox. 3, H331 Acute Tox. 4, H302; Acute Tox. 4, H312; Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21- 0000	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-211947-46-91-32- 0000	butane, pure Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-25%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27- 0000	isobutane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32- xxxx	xylene Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	5-10%

(Contd. on page 3)





Printing date 15.03.2021 Revision: 15.03.2021

Trade name: Matt Black

CAS: 107-98-2	monopropylene glycol methyl ether	l. of page <i>0-2.5%</i>
EINECS: 203-539-1 Reg.nr.: 01-2119457435-35- 0000	© Flam. Liq. 3, H226 STOT SE 3, H336	0 2.0%
CAS: 111-76-2 EINECS: 203-905-0 Reg.nr.: 01-2119475108-36- 0000	2-butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	0-2.5%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35- 0000	Solvent Naphtha (petroleum)/Aromatic. Benzene concentration is <0.1%. Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336	0-2.5%
CAS: 95-63-6 EINECS: 202-436-9 Reg.nr.: 01-2119472135-42- 0000	1,2,4-trimethylbenzene Flam. Liq. 3, H226 Aquatic Chronic 2, H411 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	0-2.5%
CAS: 103-65-1 EINECS: 203-132-9	propylbenzene Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335	0-2.5%
CAS: 108-67-8 EINECS: 203-604-4 Reg.nr.: 01-2120738996-34- 0000	mesitylene Flam. Liq. 3, H226 Aquatic Chronic 2, H411 STOT SE 3, H335	0-2.5%

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information Take affected persons out into the fresh air.
- After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact If skin irritation continues, consult a doctor.
- · After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing Rinse out mouth and then drink plenty of water.
- · 4.2 Most important symptoms and effects, both acute and delayed Headache

Dizziness

· **4.3 Indication of any immediate medical attention and special treatment needed**No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.

(Contd. on page 4)





Printing date 15.03.2021 Revision: 15.03.2021

Trade name: Matt Black

(Contd. of page 3)

· For safety reasons unsuitable extinguishing agents

Water.

Water with full jet.

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers /surface or ground water drains.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Risk of serious damage to eyes.

Open and handle receptacle with care.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

GB





Printing date 15.03.2021 Revision: 15.03.2021

Trade name: Matt Black

(Contd. of page 4)

	ontrol parameters
	ional information about design of technical facilities: No further data; see item 7. dients with limit values that require monitoring at the workplace:
	-1 propan-2-one
WEL	Short-term value: 3620 mg/m³, 1500 ppm
VV	Long-term value: 1210 mg/m³, 500 ppm
74-98	-6 propane
TWA	
	Long-term value: 1800 mg/m³, 1000 ppm
VLE	Short-term value: 3600 mg/m³, 2000 ppm
	Long-term value: 1800 mg/m³, 1000 ppm
	7-8 butane, pure
WEL	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)
75-28	-5 isobutane
TWA	Short-term value: 3800 mg/m³, 1600 ppm
	Long-term value: 1900 mg/m³, 800 ppm
1330-	20-7 xylene
WEL	Short-term value: 441 mg/m³, 100 ppm
	Long-term value: 220 mg/m³, 50 ppm
407.0	Sk; BMGV
	8-2 monopropylene glycol methyl ether
WEL	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm
	Sk
111-7	6-2 2-butoxyethanol
WEL	Short-term value: 246 mg/m³, 50 ppm
	Long-term value: 123 mg/m³, 25 ppm
	Sk, BMGV
	2-95-6 Solvent Naphtha (petroleum)/Aromatic. Benzene concentration is <0.1%.
	Long-term value: 150 mg/m³
	-6 1,2,4-trimethylbenzene
WEL	Long-term value: 125 mg/m³, 25 ppm ILV
108-6	7-8 mesitylene
WEL	Long-term value: 125 mg/m³, 25 ppm
VV	ILV
Inare	dients with biological limit values:
	20-7 xylene
	/ 650 mmol/mol creatinine
	Medium: urine





Revision: 15.03.2021 Printing date 15.03.2021

Trade name: Matt Black

(Contd. of page 5)

111-76-2 2-butoxyethanol

BMGV 240 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: butoxyacetic acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.
- · Protection of hands: Rubber gloves
- · Material of gloves Natural rubber, NR
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eve protection: Safety glasses

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol Colour: Black

· Odour: Characteristic Not determined. · Odour threshold:

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: undetermined

Initial boiling point and boiling range: -40 °C

-26 °C · Flash point:

· Flammability (solid, gaseous) Not applicable.

Not determined. Decomposition temperature:

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Not determined.

· Explosion limits:

Lower: 1.5 Vol % Upper: 13.0 Vol %

Not determined. · Vapour pressure:

· Density: Not determined

· Relative density Not determined.

(Contd. on page 7)





Printing date 15.03.2021 Revision: 15.03.2021

Trade name: Matt Black

		(Contd. of page 6)
· Vapour density · Evaporation rate	Not determined. Not applicable.	
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity: dynamic: kinematic:	Not determined. Not determined.	

No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

9.2 Other information

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.

(Contd. on page 8)





Printing date 15.03.2021 Revision: 15.03.2021

Trade name: Matt Black

(Contd. of page 7)

- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation Do not allow product to reach ground water or water course.
- Uncleaned packaging:

111 IIN Number

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport Information	n
-----------------------------------	---

· ADR, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name · ADR · IMDG · IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable	

- · 14.3 Transport hazard class(es)
- · ADR



·Class	2 5F Gases.
Labol	2.1

· IMDG, IATA



· Class	2.1
· Label	2.1

(Contd. on page 9)



Printing date 15.03.2021 Revision: 15.03.2021

Trade name: Matt Black

	(Contd. of page
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler co · EMS Number: · Stowage Code	Warning: Gases. de): - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacit of 1 litre: Category A. For AEROSOLS with capacity above 1 litre: Category B. For WAST AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Anne of Marpol and the IBC Code	ex II Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	2 D
· IMDG · Limited quantities (LQ)	1L Code: E0
Excepted quantities (EQ)	Not permitted as Excepted Quantity

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Group Standard Allocation: Aerosols Flammable Group Standard 2017

HSNO Approval Number: HSR002515

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS07
- · Signal word Danger

(Contd. on page 10)





Printing date 15.03.2021 Revision: 15.03.2021

Trade name: Matt Black

(Contd. of page 9)

· Hazard-determining components of labelling:

propan-2-one

xylene

2-butoxyethanol

1,2,4-trimethylbenzene

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Directive 2012/18/EU

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Technical Department.

(Contd. on page 11)





Revision: 15.03.2021 Printing date 15.03.2021

Trade name: Matt Black

(Contd. of page 10)

· Contact:

Mr W Broadhurst Mr N Wardlaw

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3