



P-40 XTRA

ULTRA-FINE FINISHING GLAZE

Anti-Hologram Glaze & Polish: A specially formulated Ultra fine compound using the latest DRA Technology* designed for final finish polishing to remove hologram, swirls and light defects.* **UNIQUE DRA** - (Dynamic response Abrasion) technology, incorporates micro precision oxides.

Problem Colours: Highly recommended for problem dark paint colours.

Versatile: P-40XTRA is recommended for use with: Rotary - Rotary speed - 1000 to 2000 RPM
DA Speed - 2000 to 8,000 RPM or by hand.

Easy to Use: Easy to apply, quick to buff and fast to clean.

Deep Gloss Shine: Produces a superb high gloss finish with no greasy/smearing problems, minimal drop-back.

Paint-Shop Safe: P-40XTRA is silicone AND wax free.

For use on: All automotive paint systems including, cellulose, single component and 2-pack acrylic clearcoats, MS/HS paint systems, ceramic clear coats, UV clear coats, waterborne clear coats.

Health & Safety: Silica Free. Non-flammable.

For Best Results:

By Machine: Machine Speed: 1000 - 2000 rpm (free running) speed with -40 Black Foam Polishing Pads.
Random Orbital: Machine Speed: 2000 – 8000 RPM

For vertical surfaces: charge the black soft foam pad with P-40XTRA.

For horizontal surfaces: P-40XTRA can be applied to the black foam pad and/or directly onto the panel.

Application:

1. Apply glaze to paint surface and spread to a thin even layer, using the polishing pad.
2. Using machine, polish up paint surface reducing the pressure as the film starts to clear.
3. Continue to float the surface with un-pressured pad and when clear finally remove any trace residues using microfibre polishing cloth

NB. For hologram removal it is essential to keep polishing pads clean, and separate from compounding pads. Any dust or compounding residue must be washed off vehicle before polishing.

By Hand: Use 100% fine cotton cloth to avoid introducing any scratches to sensitive paint finishes. Shake container before use. Apply to paint surface, allow polish to haze dry for a minute, then buff to a high gloss finish using non-scratch microfibre polishing cloth.

Typical Specification:

Composition	: An emulsion containing inert fillers, surfactants and thickeners.
Appearance	: Grey
Odour	: Characteristic
pH	: 8.0 ± 0.5
F.P.	: 74°C
VOC	: 79.3g/Litre
Solubility	: Miscible in water
Shelf Life	: 2 Years minimum in ambient temperature. Protect from frost.
Packaging	: 1kg

Surf-ACE P-40 Xtra is a Trade Mark of Concept Chemicals & Coatings Ltd

CODE: 711