


CONNECTION TABLE	
MTP	MDC
1	1B
2	2B
3	3B
4	4B
5	
6	
7	
8	
9	4A
10	3A
11	2A
12	1A



NOTES :

- 1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN
- 2 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM
- 3 - MDC: OM3, OM4, OM5 - IL<0.25dB , RL>30dB , 850nm & 1300nm
MDC: OS2 - IL<0.25dB, MDC/APC - RL>60dB, 1310nm & 1550nm
MDC/UPC - RL>50dB, 1310nm & 1550nm

MTP: OM3, OM4, OM5 - IL<0.35dB , RL>20dB , 850nm & 1300nm
MTP: OS2 - IL<0.35dB, RL>50dB, 1310nm & 1550nm

IL CONNECTOR VALUE ACCORDING IEC 61300-3-4 method B
RL CONNECTOR VALUE ACCORDING IEC 61300-3-6
- 4 - VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35.
END FACE GEOMETRY ACCORDING TO TELCORDIA GR-326 (Singlefiber connector)
END FACE GEOMETRY ACCORDING TO IEC 61755-3-31 (Multifiber connector - APC polished)
END FACE GEOMETRY ACCORDING TO IEC 63267-3-31 (Multifiber connector - FLAT polished)
- 5 - ASSEMBLY PACKED IN SEALED PE BAG, BULK PACK IN OUTER CARDBOARD BOX.

ORDERING CODE

Fo8X-XW9-xxx-D

D direct split version

CABLE LENGTH

9 900um tubing

W MDC (Jr)

F MTP(F) 12F, M MTP(M) 12F,

J MTP(F) PRO 12F, P MTP(M) PRO 12F

9 OS2, 3 OM3, 4 OM4, 5 OM5

o8 8F

F fanout

REVISION-DATE: A - 16.09.2020		CHANGE:	DRAWN BY, DATE: P. Gaspar 2020/09/16		TITLE: 8f MTP - MDC Direct Split							
NEW DRAWING			CHECKED BY, DATE: Pavlov/Matúš									
REVISION-DATE:		CHANGE:	APPROVED BY, DATE: I.Brestovanská		PRODUCT SPECIFICATION: -		DIMENSIONS IN MM UNLESS SPECIFIED		SCALE: NO SCALE			
REVISION-DATE: X - DD.MM.YYYY		CHANGE:		PRODUCT NUMBER: Fo8X-XW9-xxx-D				DRAWING NUMBER: 1-W-8023_1_A		SHEET NO. 1 of 1		
			A	F-rack							SIZE A3	