



- NOTES :
- 1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN
 - 2 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM
 - 3 - OM3, OM4 - IL<0.35dB , RL>50dB , 850nm & 1300nm
OS2 - IL<0.35dB, RL>50dB, 1310nm & 1550nm

IL CONNECTOR VALUE ACCORDING IEC 61300-3-4 method B
RL CONNECTOR VALUE ACCORDING IEC 61300-3-6
 - 4 - VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35.
END FACE GEOMETRY ACCORDING TO IEC 61755-3-31
 - 5 - ASSEMBLY WITH LENGTH BELOW 50MTRS PACKED IN SEALED PE BAG,
BULKPACKINOUTERCARDBOARDBOX.
LONGER ASSEMBLY THEN 50MTRS COILED ON CARDBOARD REEL,
INSERTED IN CARDBOARD BOX

ORDERING CODE

P16X-XXX-xxx

- xxx cable length [050 = 50m, 001 = 1m]
- A - Polarity A, B - Polarity B
- 6 MTP(F) 16F, 7 MTP(M) 16F
- 6 MTP(F) 16F, 7 MTP(M) 16F
- 9 OS2, 3 OM3, 4 OM4
- 16 16F
- P Patch cable

REVISION-DATE: A - 30.09.2020	CHANGE:	DRAWN BY, DATE: M.Ruzbarsky 2020/09/30	TITLE: 16f 1xMTP/APC - 1xMTP/APC Patch cable		
New drawing		CHECKED BY, DATE: Matus/Smelh.			
REVISION-DATE:	CHANGE:	APPROVED BY, DATE: L.Miskerik	PRODUCT SPECIFICATION: -	DIMENSIONS IN MM UNLESS SPECIFIED	SCALE: NO SCALE
REVISION-DATE: X - DD.MM.YYYY	CHANGE:		PRODUCT NUMBER: P16X-XXX-xxx-X	DRAWING NUMBER: 1-W-8058_1_A	SHEET NO. 1 of 1
		A	F-rack		SIZE A3