

## IP LC duplex Bulkhead adaptor

### Basic characteristics

- LC duplex Bulkhead adapter available in various colour versions of the LC duplex adaptor inside
- IP 68 Water immersion and Dust protection
- Suitable for connection of IP LC duplex connector and LC duplex standard connector
- Fixation with nut and compression seal into the designated cutout
- Chemical and UV resistance
- Intermateable with other industrial LC adaptors per IEC 61076-3-106



### Applications

- Harsh environment
- Fibre to
- Antenna
- Military
- Broadcasting
- Medical
- Oil and Gas
- Transport
- Renewable energy

### Temperature range

Operating Temperature	(-40°C/+70°C)
-----------------------	---------------

### Adaptor parameters

Compliance	Telcordia GR-326
------------	------------------

Colour of IP adaptor housing	Black
------------------------------	-------

Colour of LCD adaptor housing	Blue / Green / Beige
-------------------------------	----------------------

Insertion Loss	<0.20dB
----------------	---------

Repeatability	<0.20dB (500 times)
---------------	---------------------

### Packaging

Each adaptor in sealed PE bag, bulk pack in cardboard box.
--

\*Specifications are subject to change without notice

Kontakta oss för mer info via [info@fracksystems.se](mailto:info@fracksystems.se)