

LC patch panel – fully loaded

Basic characteristics

- Width 19"
- Height 1U
- Space for 2 back plates ready for Duralino fanout® fixation
- Available also in 2U version
- Fully loaded with pigtails



Benefits

- Exchangeable front panels and back plates
- Adjustable depth of position in rack
- 12/24x LC duplex or quad adapters

Applications

- Telecom/Datacom
- LAN/WAN Networks

Temperature range

Indoor controlled environment (-10°C /+60°C)

Parameters

Dimensions		482 x 251x 44 mm (1U)
Material		powdered coating steel
Colour		light gray RAL7035 deep black RAL9005
Capacity		up to 96 fibers
Cable entry ports	grommet/gland	2x PG13,5/M20 or 4x PG7/M12
	Duralino® fanout	2xDuralino fanout® size XL/L or 4xDuralino fanout® size S
Insertion Loss (acc. IEC 61300-3-4 method B)		<0,25dB (@1310/1550nm)
Return Loss (acc. IEC 61300-3-6)		>50dB(UPC) / >60dB(APC) (@1310/1550nm)
Identification		>30dB (@850/1300nm)
Label with unique serial number.		

Packaging

Each patch panel in cardboard box, bulk pack on palette.

* Specifications are subject to change without notice

Kontakta oss för mer information via info@fracksystems.se