




ORDERING CODE

Xo8X-VV2-xxx

xxx cable length [050 = 50m, 001 = 1m]

2 1.95mm tubing

V MDC (Sr)

V MDC (Sr)

9 OS2, 3 OM3, 4 OM4, 5 OM5

o8 8F

T trunk, G trunk with grommet*

* SHOWN TRUNK VERSION WITH GROMMET [G]

NOTES :

- 1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN
- 2 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM
- 3 - OM3, OM4, OM5 - IL<0.25dB , RL>30dB , 850nm & 1300nm
OS2 - IL<0.25dB, MDC/APC - RL>60dB, 1310nm & 1550nm
MDC/UPC - RL>50dB, 1310nm & 1550nm
IL CONNECTOR VALUE ACCORDING IEC 61300-3-4 method B
RL CONNECTOR VALUE ACCORDING IEC 61300-3-6
- 4 - VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35.
END FACE GEOMETRY ACCORDING TO TELCORDIA GR-326
- 5 - ASSEMBLY PACKED IN SEALED PE BAG, BULK PACK IN OUTER CARDBOARD BOX.

REVISION-DATE: A - 16.09.2020	CHANGE:	DRAWN BY, DATE: P. Gaspar 2020/09/16	TITLE: 8f MDC - MDC Trunk		
NEW DRAWING		CHECKED BY, DATE: Pavlov/Matúš			
REVISION-DATE:	CHANGE:	APPROVED BY, DATE: I.Brestovanská	PRODUCT SPECIFICATION: -	DIMENSIONS IN MM UNLESS SPECIFIED	SCALE: NO SCALE
REVISION-DATE: X - DD.MM.YYYY	CHANGE:	PRODUCT NUMBER: Xo8X-VV2-xxx	DRAWING NUMBER: 1-W-8021_1_A	SHEET NO. 1 of 1	
		A	F-red		SIZE A3