



CONNECTION TYPE

A - TYPE A (1-1,...16-16)

B - TYPE B (1-16,...16-1)

ORDERING CODE

V16X-XXR-xxx-X

A - TYPE A, **B** - TYPE B

xxx cable length [050 = 50m, 001 = 1m]

R - ROUND CABLE 2.3mm

A MMC/APC Female 16F, **B** MMC/APC Male 16F

A MMC/APC Female 16F, **B** MMC/APC Male 16F

9 OS2, **3** OM3, **4** OM4

16 16F

V MMC Assemblies

NOTES :

1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN

2 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM

3 - OM3, OM4 - IL<0.35dB , RL>20dB , 850nm & 1300nm
OS2 - IL<0.35dB, RL>60dB, 1310nm & 1550nm
IL CONNECTOR VALUE ACCORDING IEC 61300-3-4 method B
RL CONNECTOR VALUE ACCORDING IEC 61300-3-6

4 - VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35
END FACE GEOMETRY ACCORDING TO IEC 61755-3-31

5 - ASSEMBLY WITH LENGTH BELOW 50MTRS PACKED IN SEALED PE BAG,
BULKPACKINOUTERCARDBOARDBOX.
LONGER ASSEMBLY THEN 50MTRS COILED ON CARDBOARD REEL,
INSERTED IN CARDBOARD BOX

REVISION-DATE: A - 07.03.2024	CHANGE:	DRAWN BY, DATE: M.Ruzbarsky 07.03.2024	TITLE: 16f 1xMMC - 1xMMC cable		
New drawing		CHECKED BY, DATE: M.Bombarova			
REVISION-DATE:	CHANGE:	APPROVED BY, DATE: Matus/Smelh.	PRODUCT SPECIFICATION: QPN - 000	DIMENSIONS IN MM UNLESS SPECIFIED	SCALE: NO SCALE
REVISION-DATE: X - DD.MM.YYYY	CHANGE:	PRODUCT NUMBER: XXXX-XXX-xxx	DRAWING NUMBER: 1-W-9839_1_A	SHEET NO. 1 of 1	
		A	F-red		SIZE A3