

01x MMC – 01x MMC 16-fiber ribbon cable

Basic characteristics

- High fiber density
- APC for Multi-mode
- MMC Jr. - smaller footprint



Benefits

- Same cutout as MPO adapters
- 3x more density than traditional MPO connectors

Applications

- On-board Optics
- Transceivers

Temperature range		
Indoor controlled environment (-10°C/+60°C)		
Cable parameters		
Jacket material	N/A	
Cable construction	Bare ribbon	
Outer diameter	approx. 3,22mm x 0,34mm	
Fiber count	16	
Fiber type	OM3	
Temperature range	operation:	-40°C to +70°C
	storage:	-40°C to +85°C

01x MMC – 01x MMC 16-fiber ribbon cable

Connector parameters

	MMC Jr. MM
Compliance	Telcordia GR-1435
Color of housing	Green (APC)
Polish	Angled (APC)
Insertion Loss (acc. IEC 61300-3-4 method)	<0,35dB (@850/1300nm)
Return Loss (acc. IEC 61300-3-6)	>20dB (APC) (@850/1300nm)

Identification

Traceability label with unique serial number.

Packaging

Each assembly in plastic bag, bulk pack in cardboard box.

* Specifications are subject to change without notice

Kontakta oss för mer information på info@fracksystems.se