



NOTES :

- 1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN
- 2 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM
- 3 - OM3, OM4, OM5 - IL<0.35dB , RL>20dB , 850nm & 1300nm
OS2 - IL<0.35dB, RL>50dB, 1310nm & 1550nm
IL CONNECTOR VALUE ACCORDING IEC 61300-3-4 method B
RL CONNECTOR VALUE ACCORDING IEC 61300-3-6
- 4 - VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35
END FACE GEOMETRY ACCORDING TO IEC 61755-3-31 (Multifiber connector - APC polished)
END FACE GEOMETRY ACCORDING TO IEC 63267-3-31 (Multifiber connector - FLAT polished)
- 5 - ASSEMBLY WITH LENGTH BELOW 50MTRS PACKED IN SEALED PE BAG,
BULK PACK IN OUTER CARDBOARD BOX.
LONGER ASSEMBLY THEN 50MTRS COILED ON CARDBOARD REEL,
INSERTED IN CARDBOARD BOX

ORDERING CODE

T24X-XXX-xxx-M

- M miniflex cable
- xxx cable length [050 = 50m, 001 = 1m]
- A - Polarity A, B - Polarity B, C - Polarity C, X - Polarity X
- G MTP(F) 24F, N MTP(M) 24F, K MTP(F) PRO 24F, R MTP(M) PRO 24F
- G MTP(F) 24F, N MTP(M) 24F, K MTP(F) PRO 24F, R MTP(M) PRO 24F
- 9 OS2, 3 OM3, 4 OM4, 5 OM5
- 24 24F
- T trunk

REVISION-DATE: A - 04.06.2019		CHANGE:	DRAWN BY, DATE: P. Gašpár 2019/06/04		TITLE: 24f 1xMTP - 1xMTP Miniflex Trunk					
New drawing			CHECKED BY, DATE: Pavlov/Matúš							
REVISION-DATE:		CHANGE:	APPROVED BY, DATE: I.Brestovanská		PRODUCT SPECIFICATION: -		DIMENSIONS IN MM UNLESS SPECIFIED		SCALE: NO SCALE	
REVISION-DATE: X - DD.MM.YYYY			PRODUCT NUMBER: T24X-XXX-xxx-M		DRAWING NUMBER: -		SHEET NO. 1 of 1			
			A		F-rack				SIZE A3	