



REAR VIEW



FRONT VIEW



ADAPTERS COLOUR

MODE	MTP	SCD
OS2	GREEN	BLUE
OS2-APC	GREEN	GREEN
OM3	AQUA	AQUA
OM4	MAGENTA	MAGENTA
OM5	LIME	LIME

ORDERING CODE

M12X-XX2-BLS

F MTP female, M MTP male (direct split)
 S SC/PC, B SC/APC (direct split)
 9 OS2, 3 OM3, 4 OM4, 5 OM5
 M MTP PANEL SYSTEM

NOTES:

- 1 - OM3, OM4: IL<0.6dB AT 850nm AND 1300nm - CHANNEL VALUE ACCORDING IEC 61280-4-1 ONE-CORD REFERENCE METHOD
 RL>19.6dB AT 850nm AND 1300nm - CHANNEL GUARANTEED VALUE
 OS2: IL<0.6dB AT 1310nm AND 1550nm - CHANNEL VALUE ACCORDING IEC 61280-4-1 ONE-CORD REFERENCE METHOD
 RL>47B (UPC) AT 1310nm AND 1550nm - CHANNEL GUARANTEED VALUE
 RL>49.6B (APC) AT 1310nm AND 1550nm - CHANNEL GUARANTEED VALUE
 VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35
 END FACE GEOMETRY ACCORDING TO TELCORDIA GR-326 (Singlefiber connector)
 END FACE GEOMETRY ACCORDING TO IEC 61755-3-31 (Multifiber connector - APC polished)
 END FACE GEOMETRY ACCORDING TO IEC 63267-3-31 (Multifiber connector - FLAT polished))
- 2 - LABEL ON PRODUCT PACKAGING AND MASTER CARDBOARD BOX
- 3 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM

REVISION-DATE: A - 28.05.2014 - created a new drawing	CHANGE:	DRAWN BY, DATE: J.Špilár 2014/05/28	TITLE: 1x12f MTP to 6xSC DUPLEX MODULE		
REVISION-DATE: X - DD.MM.YYYY XXX	CHANGE:	CHECKED BY, DATE: E.Koza 2014/05/29	APPROVED BY, DATE: I.Golian 2014/05/29	PRODUCT SPECIFICATION: ID 1133	DIMENSIONS IN MM UNLESS SPECIFIED
REVISION-DATE: X - DD.MM.YYYY XXX	CHANGE:	PRODUCT NUMBER:		DRAWING NUMBER: 1-S-2954_1_A	SCALE: NO SCALE
A			F-rack		SHEET NO. 1 of 1
					SIZE A3