

# C / LC / THIN In-Ceiling



When it comes to a nice interior, how it looks is just as important as how it functions. We kept this in mind while designing our C and THIN series of in-ceiling speakers. Your speakers can be easily hidden up in your ceilings with no fear of sacrificing sound quality. These speakers feature technologies usually found in floor standing models but can disappear into the rooms décor. With a wide range of models offered, it's easy to find the perfect speaker to fit any application. Tons of features make these speakers some of the most versatile on the market. Top-of-the-line cone material, whether it's a carbon fiber, silk or aluminum, is used in every tweeter and woofer. Voice imaging control, EZGrill™, level controls, ported baskets and toggle mounting are just a few more features you can find in this series. Our CL-70v comes with 70 volt and 8 ohm settings for both commercial and home application. What's more, both the THIN and CL-70v come with backbox included, making for a quick and easy install.

<p><b>Speaker Type:</b> In-ceiling, 2 way  <b>Woofer:</b> 6.5" polypropylene  <b>Tweeter:</b> .75" mylar  <b>Power:</b> 5 - 60 watts  <b>Impedance:</b> 8 ohms  <b>70v Taps:</b> ---  <b>Freq Response:</b> 55 - 20k Hz  <b>Sensitivity:</b> 88 dB  <b>Grill Type:</b> Micromesh, aluminum</p> <p><b>Finish Dims:</b> 9.5" (240mm) diameter, 2.75" (69mm) deep  <b>Cutout Dims:</b> 8.25" (208mm) diameter</p> <p><b>Family:</b>  ARCHES</p>	<p><b>LC-6</b></p> <p>In-ceiling, 2 way            6.5" polypropylene            .75" mylar            5 - 60 watts            8 ohms            ---            55 - 20k Hz            88 dB            Micromesh, aluminum</p> <p><b>LC-8</b></p> <p>In-ceiling, 2 way            8" polypropylene            1" mylar tweeter            5 - 75 watts            8 ohms            ---            40 - 20k Hz (+/- 3dB)            89 dB (2.83 volts/1 meter, +3 dB)            Micromesh, aluminum</p> <p><b>CL-70v</b></p> <p>In-ceiling, 2 way            6.5" polypropylene            .75" silk            80 watts            8 ohm or 70V            2.5W - 25W selectable            95 - 20k Hz.            86dB            Micromesh aluminum,            backbox included            9.5" (240mm) diameter            5.9" (150mm) deep            8.25" (208mm) diameter</p> <p><b>THIN-CEILING-P</b></p> <p>in-ceiling, 2-way            5" Injected polypropylene            1" silk soft dome            5 - 75 watts            8 ohms            ---            65 - 20k Hz            90 dB            Framless steel, backbox            included            6.75" (171mm) diameter,            2.38" (60mm) deep            5.5" (140mm) diameter</p> <p><b>Family:</b>  POWELL</p>
<p><b>CP-6</b></p> <p>In-ceiling, 2 way            6.5" polypropylene            .75" silk soft dome, swivel            5 - 80 watts            8 ohms            52 - 20k Hz            90 dB            Micromesh, aluminum            9.5" (239mm) diameter,            2.75" (70mm) deep            8.25" (208mm) diameter</p> <p><b>Family:</b>  BRYCE</p>	<p><b>CP-8</b></p> <p>In-ceiling, 2 way            8" polypropylene            1" silk soft dome, swivel            5 - 100 watts            8 ohms            42 - 20k Hz            90 dB            Micromesh, aluminum            11" (280mm) diameter,            3.5" (91mm) deep            9.75" (249mm) diameter</p> <p><b>Family:</b>  BRYCE</p>