

PS Series Home Theater



PS-8



PS-10



PS-12

Powerful, low frequency bass makes the PS-Sub ideal for any home theater application or the perfect hi-fi system.

Our PS subs have a newly designed amplifier that uses a heavy duty transformer to minimize unwanted heat build up. This ensures a long-life for the amplifier. It also means very low distortion and powerful reproduction of music in your home theater.

A proprietary cellulose composite material is used for the woofer cone that is rigid, stiff, and durable, and is excellent for subwoofers. These new drivers also incorporate large magnets and voice coils which allow for high volumes and deep, rolling bass.

The cabinets feature two large, front-loaded ports located below the woofer. Ports of this size allow for more air to escape the cabinet when the subwoofer is at high volumes providing deeper bass and longer life to the subwoofer and amplifier. And, since the ports are located on the front of the subwoofer, it can be mounted into cabinetry without sacrificing any performance.

	PS-8
Enclosure Design:	Front fired, front ported subwoofer
Driver:	8" coated cellulose composite
Power:	100 watt internal amplifier
Frequency Range, LP:	35 - 150 Hz. (+/-3 dB)
Frequency Range, LFE:	35 - 380 Hz. (+/-3 dB) 130 mV @ 100W
Sensitivity:	60 - 180 Hz. continuously variable
Crossover:	low pass
Inputs:	Line level RCA, speaker level
Cabinet Dimensions:	15" (379mm) high (including feet) 11.5" (290mm) wide 13" (330mm) deep (including gill and amp)
Grill:	MDF frame with black speaker cloth
Finish:	Black vinyl, lightly textured
Family:	 UNIVERSAL

	PS-10
Enclosure Design:	Front fired, front ported subwoofer
Driver:	10" coated cellulose composite
Power:	150 watt internal amplifier
Frequency Range, LP:	30 - 150 Hz. (+/-3 dB)
Frequency Range, LFE:	25 - 380 Hz. (+/-3 dB) 131 mV @ 150W
Sensitivity:	60 - 180 Hz. continuously variable
Crossover:	low pass
Inputs:	Line level RCA, speaker level
Cabinet Dimensions:	16.88" (429mm) high (including feet) 12.25" (312mm) wide 14.88" (376mm) deep (including gill and amp)
Grill:	MDF frame with black speaker cloth
Finish:	Black vinyl, lightly textured
Family:	 UNIVERSAL

	PS-12
Enclosure Design:	Front fired, front ported subwoofer
Driver:	12" coated cellulose composite
Power:	250 watt internal amplifier
Frequency Range, LP:	30 - 150 Hz. (+/-3 dB)
Frequency Range, LFE:	20 - 380 Hz. (+/-3 dB) 151 mV @ 200W
Sensitivity:	50 - 180 Hz. continuously variable
Crossover:	low pass
Inputs:	Line level RCA, speaker level
Cabinet Dimensions:	18.88" (479mm) high (including feet) 13.75" (350mm) wide 16.38" (416mm) deep (including gill and amp)
Grill:	MDF frame with black speaker cloth
Finish:	Black vinyl, lightly textured
Family:	 UNIVERSAL